

GAS FORM-C

CLIPPER SUN



«Industry leading provider of LPG and petrochemical tonnage»

BASED ON:
OCIMF/SIGTTO
Ship Information Questionnaire for Gas Carriers
2nd Edition 1998

CONTENTS

1.	SECTION A – GENERAL INFORMATION.....	4
1.1	PRINCIPAL SHIP PARTICULARS.....	5
1.2	HULL DIMENSIONS	7
1.3	IMMERSION	7
1.4	LOADED PARTICULARS	7
1.5	PARALLEL MID-BODY DIMENSIONS.....	8
1.6	BUNKER CAPACITIES.....	8
1.7	FUEL CONSUMPTION DETAILS.....	9
1.8	MAIN ENGINE PARTICULARS	9
1.9	AUXILIARY PLANT	9
1.10	POWER/SPEED INFORMATION.....	10
1.11	THRUSTERS	10
1.12	FRESH WATER.....	10
1.13	BALLAST CAPACITIES AND PUMPS	11
1.14	MOORING	11
1.15	NAVIGATIONAL EQUIPMENT	13
1.16	COMMUNICATIONS EQUIPMENT.....	14
2.	SECTION B – CARGO SYSTEMS.....	15
2.1	GENERAL INFORMATION.....	16
2.2	CARGO TANKS.....	16
2.3	CARGO TANK CAPACITIES.....	17
2.4	LOADING RATES.....	17
2.5	DISCHARGING – GENERAL	18
2.6	DISCHARGE PRESSURE.....	18
2.7	UNPUMPABLES.....	18
2.8	VAPORISING UNPUMPABLES	18
2.9	RELIQUEFACTION PLANT	19
2.10	COOLING CAPACITY	19
2.11	CARGO TEMP. LOWERING CAPABILITY.....	19
2.12	INERT GAS.....	20
2.13	CARGO TANK INTERTING/DE-INERTING	20
2.14	GAS FREEING TO FRESH AIR	20
2.15	CHANGING CARGO GRADES	20
2.16	DECK TANK CAPACITIES	21
2.17	PRE-LOADING CONDITIONS.....	21
2.18	VAPORISER.....	21
2.19	BLOWER.....	22

2.20	CARGO RE-HEATER	22
2.21	HYDRATE CONTROL	22
2.22	CARGO MEASUREMENT	22
2.23	CARGO SAMPLING	23
2.24	CARGO MANIFOLD	24
2.25	CARGO REDUCERS	25
2.26	CONNECTION TO SHORE FOR ESD/COM SYSTEMS	25
2.27	MANIFOLD DERRICK/CRANE.....	25
2.28	STORES HANDLING	25
3.	SECTION C – MACHINERY	27
3.1	NOX FACTOR TIER II	28
3.2	NOX FACTOR TIER III.....	29
3.3	EGCS/SCRUBBER.....	30
3.4	HEAT RECOVERY	30
3.5	OTHER RELEVANT TECHNICAL INFORMATION	30
3.6	ENVIRONMENTAL/PERFORMANCE TECHNOLOGIES INSTALLED.....	31
4.	APPENDIX/DRAWINGS.....	32
4.1	CARGO PUMPS	33
4.2	BOOSTER PUMPS.....	34
4.3	RE-HEATER CAPACITY, AMMONIA.....	35
4.4	RE-HEATER CAPACITY, PROPANE	36
4.5	MOORING DIAGRAM.....	37



Solvang ASA dates back to 1936. From very modest beginnings, the shipping company has now developed into one of the world's leading transporters of LPG and petrochemical gases. Solvang ASA has its headquarters in Stavanger, with offices in Oslo and the Philippines.

Solvang has a fleet of modern and efficient vessels - all built in the accordance with the most up to date specifications and fitted with new and efficient technology. Perhaps of greater importance than the modern technology is the way in which the vessels are operated – the people onboard. Good seamanship represents the very core of our business, and we place a firm focus on this area in the form of education, working on attitudes and training.

On every single sailing, we are required to demonstrate the full range of our experience and expertise. Our strength lies in reliable, high-quality deliveries. It is our goal to maintain a steady course towards the future, at the same time as making good use of the experience we have gained.

«Industry leading provider of LPG and petrochemical tonnage»

1. SECTION A – GENERAL INFORMATION

1.1 PRINCIPAL SHIP PARTICULARS

A1	PRINCIPAL SHIP PARTICULARS		CLIPPER SUN
1.0	Date Questionnaire Completed		02.04.2020
1.1	Name of vessel		CLIPPER SUN
1.2	LR/IMO Number		IMO 9347516
1.3	Last Previous Name		Captain Leon Lemos
1.3.1	Date of Name change		30.04.2008
1.4	Second Last Name Change		N/A
1.4.1	Date of Name change		N/A
1.5	Third Last Name Change		N/A
1.5.1	Date of Name change		N/A
1.6	Fourth Last Name Change		N/A
1.6.1	Date of Name change		N/A
1.7	Flag		NIS
1.8	Port Of Registry		Stavanger
1.9	Official Number		
1.10	Call Sign		LAWL7
1.11	VSAT		+44 122 467 2592
1.12	Fleet 77		+870 765064898/99
1.13	Fax		+87 076 506 4910
1.14	Mini – M		+870773234759 FBB
1.15	E-mail		master.clipper.sun@solvangship.no
1.16	GSM Mobile		+47 907 52 616
1.17	SAT C		425971210/211
1.18	Vessel's MMSI Number		259712000
1.19	Max tank pressure	UNIT	
1.19.1	(1) Pressurized	[bar g]	
1.19.2	(2) Semi- Refrigerated	[bar g]	
1.19.3	(3) Refrigerated	[bar g]	0,25/0,45
1.20	Minimum tank temperature	UNIT	
1.20.1	(1) Pressurized	[°C]	
1.20.2	(2) Semi- Refrigerated	[°C]	
1.20.3	(3) Refrigerated	[°C]	-50
A1	OWNERSHIP AND OPERATION		
1.21	REGISTERED OWNER		P/R CLIPPER SUN II DA
1.22	Visitor's address		Strandkaien 36
1.22.1	City		N-4005 Stavanger
1.22.2	Country		Norway
1.23	Postal address		P.O. Box 90
1.23.1	City		N-4001 Stavanger
1.23.2	Country		Norway
1.24	Office Telephone Number		+47 51 84 84 00
1.25	Office Fax Number		+47 51 84 84 11
1.26	Office Telex Number		
1.27	Office e-mail Address		solvang-vlgc@solvangship.no
1.28	Number of Years Vessel Owned		11.9
1.29	NAME OF TECHNICAL OPERATOR		Solvang ASA
1.30	Visitor's address		Strandkaien 36
1.30.1	City		N-4005 Stavanger
1.30.2	Country		Norway
1.31	Postal address		P.O. Box 90
1.31.1	City		N-4001 Stavanger
1.31.2	Country		Norway
1.32	Office Telephone Number		(+47) 51 84 84 00

1.33	Office Fax Number	(+47) 51 84 84 11	
1.34	Office Telex Number		
1.35	Office e-mail Address	solvang-vlgc@solvangship.no	
1.36	Number of Years as vessel Operator	11.9	
1.37	Total number of vessels, Operator	27	
1.38	COMMERCIAL OPERATOR	Solvang ASA	
1.39	Visitor's address	Haakon VII's gt 6	
1.39.1	City	N-0121 Oslo	
1.39.2	Country	Norway	
1.40	Postal address	P.O.Box 1737 Vika	
1.40.1	City	N-0121 Oslo	
1.40.2	Country	Norway	
1.41	Office Telephone Number	(+47) 22 47 19 50	
1.42	Office e-mail Address	chartering@solvangship.no	
1.42.1	Office e-mail Address 2	operation@solvangship.no	
1.43	Number of Years as vessel Operator	11.9	
1.44	Builder	Hyundai HI	
1.45	Name of Yard Vessel Built At	Hyundai Heavy Industries co., Ltd	
1.46	Hull Number	1831	
1.47	Date Keel Laid	25.10.2007	
1.48	Date Launched	15.02.2008	
1.49	Date Delivered	30.04.2008	
1.50	Date of Completion of Major Hull Changes (If Any)	N/A	
1.51	If Changes were made, specify changes and yard	N/A	
A1	CLASSIFICATION	UNIT	CLIPPER SUN
1.52	Classification Society	[Text]	DNV GL
1.53	Class Notation	[Text]	1A1 TANKER FOR LIQUIFIED GAS
1.53.1	Cont.	[Text]	E0 BIS TMON NAUTICUS
1.53.2	Cont.	[Text]	
1.54	If Class Society Changed, Name of Previous society	[Text]	Lloyds Register
1.55	If Class Society Changed, Date of Change	[Date]	02.02.2011
1.56	Built in accordance with Regulations:		Approval recieved
1.56.1	IMO	[Yes/No]	YES
1.56.2	USCG	[Yes/No]	YES
1.56.3	RINA	[Yes/No]	NO
1.56.4	Other	[Yes/No]	NO
1.57	IMO Certification Certificate of Fitness		Approval recieved
1.57.1	IGC	[Yes/No]	YES
1.57.2	A328	[Yes/No]	NO
1.57.3	A329	[Yes/No]	NO
1.57.4	Letter of compliance	[Yes/No]	YES
1.57.5	Issued By	[Text]	DNV GL
1.58	Unattended Machinery Space certificate	[Yes/No]	Yes (24h)
A1	TONNAGES	UNIT	CLIPPER SUN
1.59	Nett Registered Tonnage	[NT]	17309
1.60	Gross Tonnage	[GT]	47552
1.61	Suez Canal Tonnage		
1.61.1	Net Tonnage	[NT]	41559.27
1.61.2	Gross Tonnage	[GT]	49849.26
1.62	Panama Canal Tonnage		
1.62.1	Net Tonnage	[NT]	
1.62.2	Gross Tonnage	[GT]	

1.2 HULL DIMENSIONS

A2	HULL DIMENSIONS	UNIT	CLIPPER SUN
2.1	Length Overall	[m]	225.3
2.2	Length Between Perpendiculars	[m]	215.0
2.3	Distance Bow to Bridge	[m]	185.0
2.4	Distance Bridge Front to Mid-Point Manifold	[m]	73.8
2.5	Distance Bow to Mid-Point Manifold	[m]	119.5
2.6	Extreme Breadth	[m]	36.6
2.7	Extreme Depth	[m]	22.0
2.8	Summer Draught	[m]	12.6
2.9	Corresponding Deadweight	[ton]	58677.0
2.10	Light Displacement/weight	[ton]	18846.0
2.11	Loaded Displacement (Summer)	[ton]	77523.0
2.12	Cargo Tank Cubic Capacity (100% full)	[m3]	82268.0
2.13	Distance from Keel to Highest Point (With mast down)	[m]	50.4
2.14	Air Draught normal ballast (With mast down)	[m]	41.2


1.3 IMMERSION

A3	IMMERSION	UNIT	CLIPPER SUN
3.1	Normal Ballast Draught	[TPC]	45.95
3.1.1	Draught	[m]	7.92
3.2	Loaded Draught	[TPC]	77.52
3.2.1	Draught	[m]	12.57

1.4 LOADED PARTICULARS

A4	LOADED PARTICULARS	UNIT	CLIPPER SUN		
4.1	Cargo:		Propane	VCM	Ammonia
4.2	Density:	[ton/m3]	0.58		0.68
4.3	Cargo	[ton]	46761.30		54444.8
4.4	Bunkers	[ton]	3560.89		3560.886956
4.5	DO	[ton]			
4.6	Fresh Water	[ton]	425.00		425
4.7	Stores/Spares	[ton]	101.3		101.3
4.8	Lube Oil	[ton]	151.7		151.7
4.9	Ballast	[ton]			
4.10	Deadweight Const.	[ton]			
4.11	Draught – Forward	[m]	9.99		11.57
4.11.1	Aft	[m]	12.83		13.46
4.11.2	Equiv.	[m]	11.41		12.51

1.5 PARALLEL MID-BODY DIMENSIONS



A5	PARALLEL MID-BODY DIMENSIONS	UNIT	CLIPPER SUN
5.1	A Manifold to FWD	[m]	109.48
5.2	B Manifold to AFT	[m]	115.79
5.3	Loaded draft equiv-		12.57
5.3.1	C Manifold to FWD side tangent line	[m]	50.3
5.3.2	D Manifold to AFT side tangent line	[m]	74.78
5.4	Ballast draft equiv.		7.62
5.4.1	E Manifold to FWD	[m]	47.88
5.4.2	F Manifold to AFT	[m]	61.05

1.6 BUNKER CAPACITIES

A6	BUNKER CAPACITIES	UNIT	CLIPPER SUN
6.1	HFO	[Grade]	IFO 380 (Standard)
6.1.1	Capacity @ 100 %	[m3]	2962.1
6.2	LSHFO	[Grade]	N/A
6.2.1	Capacity @ 100 %	[m3]	N/A
6.3	Diesel Oil	[Grade]	DO
6.3.1	Capacity @ 100 %	[m3]	698.6

1.7 FUEL CONSUMPTION DETAILS

Average speed and consumption, based on max force 4 Beaufort and 15% Sea Margin.

Vessel use mainly HFO for all consumers. DO/GO for INCN and when Rules & Regulations demands it for other consumers

A7	FUEL CONSUMPTION DETAILS	UNIT	CLIPPER SUN
7.1	LOADED CONDITION		*About
7.2	Average speed over 12 months	[kn]	16.5
7.3	Average consumption, Main engine	[ton/day]	56.0
7.4	Consumption, AUX		
7.4.1	Propane/Ammonia	[ton/day]	4 – 8
7.4.2		[ton/day]	
7.5	Average consumption, AUX		
7.5.1	Propane/Ammonia	[ton/day]	5.5
7.5.2		[ton/day]	
7.6	BALLAST CONDITION		
7.7	Average speed over 12 months	[kn]	16.5
7.8	Average consumption, Main engine	[ton/day]	54.0
7.9	Average consumption, AUX	[ton/day]	4
7.10	PORT/IDLE		
7.11	Average consumption, AUX, Loading	[ton/day]	8
7.12	Average consumption, AUX, Discharging	[ton/day]	5.5
7.13	Average consumption, AUX, Idle	[ton/day]	4
7.14	Average consumption, Boiler (depending on weather)	[ton/day]	2,0-3,0
7.15	OTHER		
7.16	INCN (When operating) - MDO/MGO	[ton/day]	0.2
7.17	IGG-plant (When operating)	[ton/day]	0.2
7.18	ME CONSUMPTION GRAPH/KNOTS		LOADED BALLAST
7.18.1	16,5 knots	[ton/day]	56.0 54.0
7.18.2	16 knots	[ton/day]	51.0 49.0
7.18.3	15 knots	[ton/day]	43.0 41.0
7.18.4	14 knots	[ton/day]	38.0 36.0
7.18.5	12 knots	[ton/day]	31.0 29.0

**Consumption of AUX will increase with 0,2-1,0 MT/24h when systems for exhaust gas cleaning is running, depending on sulfur content in fuel oil, load of engines, alkalinity, degree of cleaning, etc

1.8 MAIN ENGINE PARTICULARS

A8	MAIN ENGINE PARTICULARS	UNIT	CLIPPER SUN
8.1	Main Engine Make and Type	[Text]	HYUNDAI-B&W 6S60MC-C
8.2	No of Units	Pcs	1
8.3	Maximum Continuous Rating (MCR)	[kW]	13735
8.3.1	RPM	[RPM]	105
8.4	Total Available Power	kW	13 735
8.5	Normal service Power	kW	12 200

1.9 AUXILIARY PLANT

A9	AUXILIARY PLANT	UNIT	CLIPPER SUN
9.1	Make and Type of Auxiliary Generators	[Text]	HYUNDAI-MAN B&W, L28/32H
9.2	Main Generators	[Pcs]	
9.2.1	No of Units	[Pcs]	4
9.2.2	Maximum Generator Output per Unit	[kW]	1 260
9.3	Generators, other	[Yes/No]	NO

9.3.1	No of Units	[Pcs]	N/A
9.3.2	Maximum Generator Output per Unit	[kW]	N/A
9.4	Shaft Generator	[kW]	N/A
9.5	Total Available Power	[kW]	5040
9.6	Emergency Generator	[kW]	188
9.7	Emergency Fire Pump	[Text]	
9.7.1	Type	[Text]	Vertical Centrifugal
9.7.2	Delivery Pressure	[Bar]	10
9.7.3	Motive Power	[Text]	Electric
9.7.4	If Electrical, Indicate Power Required in kW	[kW]	55
9.8	Steering Gear Type		Cylinder
9.8.1	kW to Steer the Vessel with One Pump Unit	[kW]	45

1.10 POWER/SPEED INFORMATION

A10	POWER/SPEED INFORMATION	UNIT	CLIPPER SUN
10.1	Trial Data		
10.1.1	NCR	[kW]	11 693
10.1.2	MCR	[kW]	13 270
10.1.3	Speed	[kn]	18.807
10.1.4	Draught	[m]	7.2
10.2	Normal Service Speed		
10.2.1	NCR	[kW]	11693
10.2.2	MCR	[kW]	13270
10.2.3	Speed	[kn]	16.5
10.2.4	Draught	[m]	7,8/11,5

1.11 THRUSTERS

A11	THRUSTERS	UNIT	CLIPPER SUN
11.1	Make and Type	[Text]	N/A
11.2	No. Installed	[Pcs]	N/A
11.3	Location and Rated Bollard Pull or kW output	[kW]	N/A

1.12 FRESH WATER

A12	FRESH WATER	UNIT	CLIPPER SUN
12.1	Capacity of Distilled Tanks	[ton]	425.00
12.2	Capacity of F/D.W. Ts	[ton]	425.00
12.3	Daily Consumption	[ton/day]	8.00
12.4	Daily Evaporator Output	[ton/day]	26.00

1.13 BALLAST CAPACITIES AND PUMPS

A13	BALLAST CAPACITIES AND PUMPS	UNIT	CLIPPER SUN	
13.1	Tank Capacities		Capacity [m3]	Tanks [Pcs]
13.1.1	Forepeak	[Col]	1 681.30	1
13.1.2	Wing or Side tanks	[Col]	8524	8
13.1.3	Aft Peak	[Col]	1323.6	1
13.1.4	Double bottom tanks	[Col]	12111	8
13.1.5	Other	[Col]		
13.1.6	Total	[Col]	23 640.30	18
13.2	Ballast Pumps			
13.2.1	Capacity per pump	[m3/h]	800	
13.2.2	Model	[Text]	FEWV-300-2D	
13.2.3	Type	[Text]	Electric	
13.2.4	Setting	[Text]	Vertical Centrifugal	
13.3	No of Pumps	[Pcs]	2	
13.4	Total Capacity	[m3/h]	1600	
13.5	Location	[Text]	Engine Room	
13.6	Control Location	[Text]	Cargo Control Room	

1.14 MOORING

A14	MOORING EQUIPMENT	UNIT	CLIPPER SUN			
14.1	Mooring wires (On drums)		FWD	FWD DECK	AFT DECK	POOP
14.1.1	Number	[Pcs]				
14.1.2	Diameter	[mm]				
14.1.3	Length	[m]				
14.1.4	Maximum Breaking Load	[ton]				
14.2	Mooring wire tails		FWD	FWD DECK	AFT DECK	POOP
14.2.1	Number	[Pcs]				
14.2.2	Type	[Text]				
14.2.3	Diameter	[mm]				
14.2.4	Length	[m]				
14.2.5	Maximum Breaking Load	[ton]				
14.3	Mooring ropes (On drums)		FWD	FWD DECK	AFT DECK	POOP
14.3.1	Number	[Pcs]	6	2	2	6
14.3.2	Type	[Text]	B5 YARN	D-FLEX	B5 YARN	B5 YARN
14.3.3	Diameter	[mm]	60	64	60	60
14.3.4	Length	[m]	220	220	220	220
14.3.5	Maximum Breaking Load	[ton]	78.5	78.6	79.2	78.5
14.4	Mooring winches		FWD	FWD DECK	AFT DECK	POOP
14.4.1	Number	[Pcs]	2	2	1	3
14.4.2	[S]ingle/[D]ouble drums	[S/D]	Double	Double	Double	Double
14.4.3	Split drums	[Yes/No]	YES	YES	YES	YES
14.4.4	Motive power	[Text]	Hydraulic	Hydraulic	Hydraulic	Hydraulic
14.4.5	Heaving power	[ton]	20	20	20	20
14.4.6	Brake capacity	[ton]	47.2	47.2	47.2	47.2
14.4.7	Hauling speed	[m/s]	0.25	0.25	0.25	0.25
14.5	Wires/ropes not on drums		WIRES	ROPES	EM'GENCY	
14.5.1	Number	[Pcs]		8		
14.5.2	Type	[Text]		D-FLEX		
14.5.3	Diameter	[mm]		64		
14.5.4	Length	[m]		220		
14.5.5	Maximum Breaking Load	[ton]		78.6		

A14	ANCHORS AND WINDLASSES	UNIT	CLIPPER SUN
14.5.1	Windlass Motive Power (e.g. Steam, Hydraulic)	[Text]	Hydraulic
14.5.2	Hauling Power	[ton]	20
14.5.3	Brake Holding Power	[ton]	47.2
14.5.4	Anchor Type	[Text]	High Holding Power
14.5.5	Weight	[kg]	8 350
14.5.6	Is Spare Carried	[Yes/No]	YES
14.5.7	Cable Diameter	[mm]	81
14.5.8	No of Shackles Port	[Pcs]	12
14.5.9	No of Shackles Starboard	[Pcs]	13
14.6	TOWING EQUIPMENT		
14.6.1	Is Ship fitted with a Towing Bracket AFT(drum)	[Yes/No]	YES
14.6.2	If Yes, state SWL	[ton]	200
14.6.3	Is Towing Chain provided	[Yes/No]	YES
14.6.4	Dimensions of Towing Wire – Diameter	[mm]	80
14.6.5	Length	[m]	100
14.7	Windage on Ballast Draught		
14.7.1	End-on	[m2]	956
14.7.2	Lateral	[m2]	3970

Mooring diagram is provided in the appendix.

1.15 NAVIGATIONAL EQUIPMENT

A15	NAVIGATIONAL EQUIPMENT	UNIT	CLIPPER SUN
15.1	Magnetic Compass	[Yes/No]	YES
15.2	Off Course Alarm – Magnetic	[Yes/No]	YES
15.3	Gyro Compass	[Yes/No]	YES
15.3.1	Specify number	[Pcs]	2
15.4	Off Course Alarm – Gyro	[Yes/No]	YES
15.5	Bridge Repeaters	[Yes/No]	YES
15.5.1	Specify Number	[Pcs]	4
15.6	Radar 3 GHz	[Yes/No]	YES
15.7	Radar 9 GHz	[Yes/No]	YES
15.8	Are Radars Gyro Stabilized	[Yes/No]	YES
15.9	Radar Plotting Equipment	[Yes/No]	YES
15.10	ARPA	[Yes/No]	YES
15.11	ECDIS (Electric Display and Information System)	[Yes/No]	YES
15.11.1	Make/Type	[Text]	Transas
15.12	Depth Echo Sounder with Recorder	[Yes/No]	YES
15.13	Depth Echo Sounder without Recorder	[Yes/No]	NO
15.14	Speed/Distance Indicator	[Yes/No]	YES
15.15	Doppler Log	[Yes/No]	YES
15.16	Speed of Approach Doppler	[Yes/No]	NO
15.17	Rudder Angle Indicator	[Yes/No]	YES
15.18	Rudder Angle Indicator on Each Bridge Wing	[Yes/No]	YES
15.19	R.P.M Indicator	[Yes/No]	YES
15.20	R.P.M Indicator on Each Bridge Wing	[Yes/No]	YES
15.21	Controllable Propeller Pitch Indicator	[Yes/No]	NO
15.22	Thruster (s) indicator	[Yes/No]	NO
15.23	Rate of turn Indicator	[Yes/No]	YES
15.24	Radio Direction Finder	[Yes/No]	NO
15.25	NAVTEX Receiver	[Yes/No]	YES
15.26	GPS	[Yes/No]	YES
15.27	Transit SATNAV	[Yes/No]	NO
15.28	DECCA navigator	[Yes/No]	NO
15.29	Omega	[Yes/No]	NO
15.30	Loran C	[Yes/No]	NO
15.31	Weather Route System	[Yes/No]	YES
15.32	Sextant(s)	[Yes/No]	YES
15.33	Signal Lamp ALDIS	[Yes/No]	YES
15.34	Anemometer	[Yes/No]	YES
15.35	Engine Order Recorder	[Yes/No]	YES
15.36	Course Recorder	[Yes/No]	YES
15.37	Steering motor controls controls fitted on bridge wings	[Yes/No]	NO
15.38	Is bridge Equipped with a “Dead Man” Alarm Equipment	[Yes/No]	YES
15.39	What chart outfit coverage is provided	[Yes/No]	
15.39.1	Worldwide	[Yes/No]	YES
15.39.2	Limited	[Yes/No]	NO
15.39.3	If Limited Please Indicate	[Text]	
15.40	Formal Chart Correction System in use	[Yes/No]	YES
15.41	Electronic Chart System in use	[Yes/No]	YES

1.16 COMMUNICATIONS EQUIPMENT

A16	COMMUNICATIONS EQUIPMENT	UNIT	CLIPPER SUN
16.1	Main Transmitted Including Radio Telephone Distress Frequency	[Yes/No]	YES
16.2	Main Receiver Including Radio Telephone Distress Frequency	[Yes/No]	YES
16.3	Radio Telephone Distress Frequency Watch Receiver	[Yes/No]	YES
16.4	Main Radio Antenna	[Yes/No]	YES
16.5	Reserve Radio Antenna	[Yes/No]	NO
16.6	Main and Reserve Installations Electrically Separate and Independent	[Yes/No]	YES
16.7	2182 kHz Bridge auto Alarm	[Yes/No]	YES
16.8	Alarm Signal Generating Device	[Yes/No]	YES
16.9	VHF Radio (s)	[Yes/No]	YES
16.9.1	Specify Number	[Pcs]	3
16.10	Portable VHF/UHF Radios	[Yes/No]	YES
16.10.1	Specify Type and Number	[Pcs]	3(OFE)
16.11	Are Sets Intrinsically Safe	[Yes/No]	YES
16.12	Inmarsat Satellite System	[Yes/No]	NO
16.13	Specify System Type A, B, C, F or VSAT	[Text]	
16.14	Is the ship equipped as per GMDSS Requirements	[Yes/No]	YES
16.15	If Yes, which area of operation is vessel certified to operate in	[Text]	A1, A2, A3
16.15.1	EPIRB	[Yes/No]	YES
16.15.2	SARTS	[Yes/No]	YES
16.16	Emergency Lifeboat Transceiver	[Yes/No]	NO
16.17	At least Three Survival craft Two-way Radio Telephone Apparatus	[Yes/No]	YES
16.18	Full Set of Publications	[Yes/No]	YES

2. SECTION B – CARGO SYSTEMS

2.1 GENERAL INFORMATION

B1	CARGO - GENERAL INFORMATION		CLIPPER SUN	
1.1	List Products Which the Ship is Certified to Carry			
1.1.1	1.	Anhydrous Ammonia		
1.1.2	2.	1,3-Butadiene		
1.1.3	3.	Butane (ISO and normal)		
1.1.4	4.	Butylene		
1.1.5	5.	Propane (pure and commercial)		
1.1.6	6.	Propylene		
1.1.7	7.	Butane and Propane Mixtures		
1.1.8	8.			
1.1.9	9.			
1.1.10	10.			
1.1.11	11.			
1.1.12	12.			
1.1.13	13.			
1.1.14	14.			
1.1.15	15.			
1.1.16	16.			
1.1.17	17.			
1.1.18	18.			
1.1.19	19.			
1.1.20	20.			
1.1.21	21.			
1.1.22	22.			
1.1.23	23.			
1.1.24	24.			
1.2	Transport and Carriage Condition		UNIT	
1.3	Minimum Allowable Tank Temperature		[Celsius]	-50
1.3.1	Maximum Allowable Tank Pressure (Seagoing setting)		[bar g]	0.25
1.3.2	Maximum Allowable Tank Pressure (Harbour setting)		[bar g]	0.45
1.4	Grades which can be Loaded or Discharged Simultaneously		[Pcs]	2
1.5	Grades which can be Transported Simultaneously		[Pcs]	2
1.6	Number of Products Re-liquefied Simultaneously		[Pcs]	2
1.7	State Natural Tank Segregations (Possible combinations)		UNIT	
1.7.1	1.		[Tank]	1+3 & 2+4
1.7.2	2.		[Tank]	2 & 1+3+4
1.7.3	3.		[Tank]	1+2+3+4

2.2 CARGO TANKS

B2	CARGO TANKS	UNIT	CLIPPER SUN
2.1	Cargo Tanks		
2.1.1	Type	[Text]	NV 4-4-MOD32
2.1.2	Material	[Text]	Carbon Manganese LT
2.2	Maximum Allowable Relief Valve setting	[bar g]	0.45
2.3	Safety Valve Set Pressure – If Variable Give Range of Pilot Valves		
2.3.1	Seagoing setting	[bar g]	0.25
2.3.2	Harbour setting	[bar g]	0.45
2.4	Maximum Vacuum	[bar g]	-0.05
2.5	Maximum Cargo Density (98% full)	[kg/m3]	690
2.6	Maximum Rate of Cool-Down	[C/h]	10

2.7	State any Limitations regarding Partially Filled Tanks	[Text]	None
2.7.1	Cont.	[Text]	
2.8	State Allowable Combinations of Filled and Empty Tanks	[Text]	
2.8.1	Cont.	[Text]	

2.3 CARGO TANK CAPACITIES

B3	CARGO TANK CAPACITIES	UNIT	CLIPPER SUN				
3.1	Capacity	Tank	1	2	3	4	Total
3.1.1	100 %	[m3]	17918	21834	21826	20689	82267
3.1.2	98 %	[m3]	17560	21397	21389	20275	80622
3.2	Cargo						
3.2.1	iso-butane	[ton]	10430	12710	12705	12043	47889
3.2.2	Propane	[ton]	10185	12410	12406	11760	46761
3.2.3	Butadiene	[ton]	11431	13930	13925	13199	52485
3.2.4	Propylene	[ton]	10711	13052	13048	12368	49179
3.2.5	Ammonia	[ton]	11941	14550	14545	13787	54823
3.2.6	Butylene/Butenes	[ton]	10430	12710	12705	12043	47889
3.2.7	n-butane	[ton]	10553	12860	12855	12185	48454
3.2.8	Ethylene	[ton]					

- Cargoes may not be applicable for vessel. Check which cargoes the vessel is certified to carry.

2.4 LOADING RATES

VR = Vapour Return, W/O VPR = Without Vapour Return

B4	LOADING RATES	UNIT	CLIPPER SUN			
			REFRIGERATED		PRESSURE	
4.1	Cargo	[m3/h]	VR	W/O VR	VR	W/O VR
4.1.1	1 Propylene	[m3/h]		2928		
4.1.2	2 Propane	[m3/h]		2784		
4.1.3	3 Ammonia	[m3/h]		3264		
4.1.4	4 Iso butane (0°C)	[m3/h]		2851		
4.1.5	5 Propane (0°C)	[m3/h]				
4.1.6	6 Propane (10°C)	[m3/h]				
4.1.7	7 Propane (20°C)	[m3/h]				
4.1.8	8 Propane (30°C)	[m3/h]				
4.1.9	9	[m3/h]				
4.1.10	10	[m3/h]				
4.1.11	11	[m3/h]				
4.1.12	12	[m3/h]				
4.1.13	13	[m3/h]				
4.1.14	14	[m3/h]				
4.1.15	15	[m3/h]				
4.1.16	16	[m3/h]				
4.1.17	17	[m3/h]				
4.1.18	18	[m3/h]				
4.1.19	19	[m3/h]				
4.1.20	20	[m3/h]				

2.5 DISCHARGING – GENERAL

Pumping curves for cargo main pumps and booster pumps are given in the appendix.

B5	DISCHARGING – GENERAL	UNIT	CLIPPER SUN
5.1	Cargo Pumps	[Text]	Deepwell
5.1.1	Type of Pumps	[Text]	Centrifugal
5.1.2	Number per Tank	[Pcs]	2
5.1.3	Rate (per pump)	[m3/h]	600
5.1.4	Delivery Head	[mlc]	120
5.1.5	Maximum Density	[kg/m3]	690
5.2	Booster Pumps		
5.2.1	Type of Pumps	[Text]	Centrifugal
5.2.2	Number	[Pcs]	2
5.2.3	Rate (per pump)	[m3/h]	600
5.2.4	Delivery Head	[mlc]	115
5.2.5	Maximum Density	[kg/m3]	690

2.6 DISCHARGE PRESSURE

B6	DISCHARGE PERFORMANCE	UNIT	CLIPPER SUN
6.1	Fully Refrigerated, Full Cargo Discharge Times (all pumps):		VR W/O VR
6.1.1	Manifold Back Pressure (1 kg/cm2) x	[h]	17 17
6.1.2	Manifold Back Pressure (5 kg/cm2) x	[h]	18 18
6.1.3	Manifold Back Pressure (10 kg/cm2) x	[h]	70 70
6.2	Pressurized, Full Cargo Discharge Times (all pumps):		VR W/O VR
6.2.1	Manifold Back Pressure (1 kg/cm2) x	[h]	17 17
6.2.2	Manifold Back Pressure (5 kg/cm2) x	[h]	18 18
6.2.3	Manifold Back Pressure (10 kg/cm2) x	[h]	70 70

x = Based on largest single tank volume

^ = Based on discharging tanks one at a time

2.7 UNPUMPABLES

B7	UNPUMPABLES	UNIT	CLIPPER SUN
7.1	Unpumpables, liquid		
7.1.1	Tank 1	[m3]	15
7.1.2	Tank 2	[m3]	15
7.1.3	Tank 3	[m3]	15
7.1.4	Tank 4	[m3]	15
7.1.5	Total	[m3]	60

2.8 VAPORISING UNPUMPABLES

B8	VAPORISING UNPUMPABLES	UNIT	CLIPPER SUN
8.1	Process Used	[Text]	Hot Gas/Puddle heating
8.2	Time to Vaporize Liquid Unpumpables After Discharge:		
8.2.1	Propane	[h]	24
8.2.2	iso-Butane	[h]	24
8.2.3	n-Butane	[h]	26
8.2.4	Ammonia	[h]	52
8.2.5		[h]	

2.9 RELIQUEFACTION PLANT

B9	RELIQUEFACTION PLANT	UNIT	CLIPPER SUN
9.1	Plant Design Conditions		
9.1.1	Air Temperature	[°C]	50
9.1.2	Sea Temperature	[°C]	36
9.2	Plant Type		
9.2.1	Single Stage/Direct	[Yes/No]	YES
9.2.2	Two Stage / Direct	[Yes/No]	YES
9.2.3	Three Stage / Direct	[Yes/No]	YES
9.2.4	Coolant Type	[Text]	Seawater
9.3	Compressors		
9.3.1	Type	[Text]	Sulzer + Burckhardt
9.3.2	Model	[Text]	3K-140-3A
9.3.3	Number	[Psc]	4
9.3.4	Capacity (per unit)	[m3/h]	1341
9.3.5	Are they oil free?	[Yes/No]	YES

2.10 COOLING CAPACITY

B10	COOLING CAPACITY	UNIT	CLIPPER SUN	
10.1	State Cooling Capacity (per compressor, 2-stage @ - 0.4 bar g)		SW 36 [°C]	SW 15 [°C]
10.1.1	1 Propane @ -42 [°C]	[kcal/h]	320000	375000
10.1.2	2 Com. Propane (5 mol.% ethane) @ -42 [°C]	[kcal/h]	245000	295 000
10.1.3	3 Propane @ -20 [°C]	[kcal/h]		
10.1.4	4 Propane @ -5 [°C]	[kcal/h]		
10.1.5	5 Iso-Butane @ -5 [°C]	[kcal/h]	560000	680 000
10.1.6	6 Ammonia @ -33 [°C]	[kcal/h]	450000	505 000
10.1.7	7 VCM @ -11[°C]	[kcal/h]		

2.11 CARGO TEMP. LOWERING CAPABILITY

B11	CARGO TEMPERATURE LOWERING CAPABILITY	UNIT	CLIPPER SUN
11.0	Time taken to lower the temp of:		
11.1	Propane from ...0 [°C] to -42 [°C]	[h]	
11.2	-5[°C]to -42[°C]	[h]	
11.3	-38[°C] to -42[°C]	[h]	142
11.4	+20[°C] to -42[°C]	[h]	
11.5	+10[°C] to -42[°C]	[h]	
11.6	Iso-Butane from +20[°C] to -0.5[°C]	[h]	
11.7	+10[°C] to -0.5[°C]	[h]	
11.8	+10[°C] to -5[°C]	[h]	
11.9	-5[°C] to -12[°C]	[h]	127
11.10	Ammonia from -30[°C] to -33[°C]	[h]	152
11.11	Propylene from -42[°C] to -47[°C]	[h]	175

2.12 INERT GAS

B12	INERT GAS	UNIT	CLIPPER SUN
12.1	Main IG Plant		
12.1.1	Type of System	[Text]	Stoichiometric comb.
12.1.2	Capacity	[m3/h]	5300
12.1.3	Type of Fuel Used	[Text]	MDO/MGO
12.1.4	Composition of I.G.		
12.1.5	Max O2	[%]	0.5
12.1.6	Max CO2	[%]	
12.1.7	Max Nox	[%]	0.01
12.1.8	Max N2	[%]	Balance
12.2	Lowest Dewpoint Achievable	[°C]	-40
12.3	Used for	[Text]	Void spaces/change of grade
12.4	Auxiliary IG or Nitrogen Plant		N/A
12.4.1	Type of System	[Text]	N/A
12.4.2	Capacity	[m3/h]	N/A
12.5	Lowest Dewpoint Achievable	[°C]	N/A
12.6	Used for	[Text]	N/A
12.7	Nitrogen generator installed?	[Yes/No]	NO
12.7.1	Liquid storage Capacity	[m3]	N/A
12.7.2	Daily Boil-Off Loss	[m3]	N/A
12.7.3	Maximum Supply Pressure	[Bar]	N/A
12.7.4	Supply Capacity	[m3/h]	N/A
12.7.5	Used For	[Text]	N/A
12.7.6	HP Nitrogen	[Nm3]	N/A

2.13 CARGO TANK INTERTING/DE-INERTING

B13	CARGO TANK INTERTING/DE-INERTING	UNIT	CLIPPER SUN
13.1	Time Taken From Fresh Air to Under 5% O2 at -25oC Dewpoint	[h]	26
13.2	Time taken from cargo Vapor to Fully Inert at - 25oC Dewpoint when:		
13.2.1	IG density less than product	[h]	18
13.2.2	IG density greater than product	[h]	18

2.14 GAS FREEING TO FRESH AIR

B14	GAS FREEING TO FRESH AIR	UNIT	CLIPPER SUN
14.1	Plant Used	[Text]	Blower
14.1.1	Number of fans	[Pcs]	2
14.1.2	Total capacity	[m3/h]	20000
14.2	Time taken from Fully Inert Condition to Fully Breathable Air	[h]	17

2.15 CHANGING CARGO GRADES

The table below show the number of hours needed to change grades from the removal of unpumpables to tanks fit to load. The quantity of inert gas consumed during the operation is also indicated.

B15	CHANGING CARGO GRADES	UNIT	CLIPPER SUN	
15.1	From propane to:		[h]	[m3]
15.1.1	Iso-butane	[COL]	136	95400
15.1.2	Ammonia	[COL]	237	95400
15.2	From Iso-butane to:		[h]	[m3]
15.2.1	Propane	[COL]	91	95400
15.2.2	Ammonia	[COL]	176	95400
15.3	From ammonia to:		[h]	[m3]
15.3.1	Propane	[COL]	215	35510
15.3.2	Iso-butane	[COL]	144	95400

2.16 DECK TANK CAPACITIES

B16	DECK TANK CAPACITIES	UNIT	CLIPPER SUN
16.1	Deck tank	[Yes/No]	NO
16.2	Deck tank capacities		
16.2.1	1 Propane	[ton]	N/A
16.2.2	2 Ammonia	[ton]	N/A
16.2.3	3 Ethylene	[ton]	N/A
16.3	Maximum Allowable Relief Valve Setting	[bar g]	N/A
16.4	Lowest Permissible Temperature	[°C]	N/A
16.5	Materials	[Text]	N/A

2.17 PRE-LOADING CONDITIONS

The table below indicates time and quantity of coolant required to cool down cargo tanks from ambient temperature and fully gassed up state sufficient to allow loading to commence.

B17	PRE-LOADING CONDITIONS	UNIT	CLIPPER SUN		
17.1	Product		Quantity [ton]	VPR [h]	W/O VPR [h]
17.1.1	Propane	[COL]	420	12	36
17.1.2	Butane	[COL]	500	5	14
17.1.3	Butadiene	[COL]	500	10	20
17.1.4	Propylene	[COL]	420	12	36
17.1.5	Ammonia	[COL]	600	12	36
17.1.6	VCM	[COL]			

2.18 VAPORISER

B18	VAPORISER	UNIT	CLIPPER SUN
18.1	Type of Vaporizer	[Text]	Shell and tube
18.2	Number Fitted	[Pcs]	1
18.3	Capacity (per unit) – Propane	[Nm3/h]	5000
18.3.1	Liquid Supply rate	[m3/h]	15
18.3.2	Delivery temperature	[°C]	0.7
18.4	Capacity (per unit) – Ammonia	[Nm3/h]	4800
18.4.1	Liquid Supply rate	[m3/h]	15
18.4.2	Delivery temperature	[°C]	0.7
18.5		[Nm3/h]	
18.5.1		[m3/h]	
18.5.2		[°C]	

2.19 BLOWER

B19	BLOWER	UNIT	CLIPPER SUN
19.1	Type of Blower	[Text]	Flame proof motor driven fixed type centrifugal X 2
19.2	Number fitted	[Pcs]	2
19.3	Rated Capacity (per unit)	[Nm ³ /h]	10000
19.4	Delivery Pressure	[Bar]	0.1

2.20 CARGO RE-HEATER

Cargo re-heater capacities are given in the appendix.

B20	CARGO RE-HEATER	UNIT	CLIPPER SUN
20.1	Type of re-heater	[Text]	Shell/tube
20.2	Number Fitted	[Pcs]	1
20.3	Heating Medium	[Medium]	Seawater
20.4	Discharge rates, SW = 15[°C], to raise product temperature:		
20.4.1	Propane from -42[°C] to 0[°C]	[ton/h]	340
20.4.2	Ammonia from -33[°C] to 0[°C]	[ton/h]	260
20.5	Cargo Heater Curve:	[Yes/No]	YES

2.21 HYDRATE CONTROL

B21	HYDRATE CONTROL	UNIT	CLIPPER SUN
21.1	Type of Depressant	[Medium]	Ethanol
21.2	Depressant Freezing Point Temperature	[°C]	-114
21.3	Max capacity of depressant	[Liter]	1200
21.4	Means of Injection	[Text]	Hand pump
21.5	Any other system used	[Text]	

2.22 CARGO MEASUREMENT


B22	CARGO MEASUREMENT	UNIT	CLIPPER SUN
22.1	Level Gauges		
22.1.1	Are level gauges Local or Remote	[Text]	Remote
22.1.2	Manufacturer	[Text]	HENRI
22.1.3	Type	[Text]	Float
22.1.4	Rated Accuracy	[-]	± 5 mm
22.1.5	Certifying Authority	[Text]	NKKK
22.2	Temperature Transmitter		
22.2.1	Manufacturer	[Text]	BEKA
22.2.2	Type	[Text]	CAPILLARY
22.2.3	Rated Accuracy	[-]	0.3
22.2.4	Certifying Authority	[Text]	NKKK
22.3	Pressure Transmitter		
22.3.1	Manufacturer	[Text]	BEKA
22.3.2	Type	[Text]	Bourdon
22.3.3	Rated Accuracy	[-]	0.993
22.3.4	Certifying Authority	[Text]	NKKK

22.4	Oxygen Analyzer		
22.4.1	Manufacturer	[Text]	OPIS 02000
22.4.2	Type	[Text]	Zirconia oxide probe
22.4.3	Lowest Level Measurable		
22.5	Fixed Gas Analyzer		
22.5.1	Manufacturer	[Text]	MARTEK MM5000
22.5.2	Type	[Text]	Catalytic
22.6	Cargo Tank Calibration Tables		
22.6.1	Are Cargo Tank Calibration tables available	[Yes/No]	YES
22.6.2	Measuring Company	[Text]	Celeb Brett - KIMSCO
22.6.3	Certifying Authority	[Text]	NKKK
22.6.4	Calibration calculated tocm ½ cm.....	[Yes/No]	NO
22.6.5	Tables established tocmcm.....mm	[Yes/No]	1 cm
22.6.6	Trim and List corrections Available	[YES/NO]	YES
22.6.7	Temperature Corrections available	[YES/NO]	YES
22.6.8	Float Gauge Tape Corrections Available	[YES/NO]	YES

2.23 CARGO SAMPLING

B23	CARGO SAMPLING	UNIT	CLIPPER SUN
23.1	Cargo tank sample level	[Tank]	1 2 3 4
23.1.1	Top	[Yes/No]	Yes Yes Yes Yes
23.1.2	Middle	[Yes/No]	Yes Yes Yes Yes
23.1.3	Bottom	[Yes/No]	Yes Yes Yes Yes
23.2	Can sample be drawn from?		
23.2.1	Tank Vapor Outlet	[Yes/No]	YES
23.2.2	Manifold Liquid Line	[Yes/No]	YES
23.2.3	Manifold Vapor Line	[Yes/No]	YES
23.2.4	Pump Discharge Line	[Yes/No]	YES
23.3	State connection		
23.3.1	Type	[Text]	Screw
23.3.2	Size	[Inch]	0.5

2.24 CARGO MANIFOLD



B24	CARGO MANIFOLD	UNIT	CLIPPER SUN			
24.1	Distance from center of manifold to:					
24.1.1	Stern	[m]	115.79			
24.1.2	Bow	[m]	109.48			
24.1.3	A	[mm]	7625			
24.1.4	B	[mm]	5625			
24.1.5	C	[mm]	3375			
24.1.6	D	[mm]	1125			
24.1.7	E	[mm]	1125			
24.1.8	F	[mm]	3375			
24.1.9	G	[mm]	5625			
24.1.10	H	[mm]	7625			
24.2	Flange		Duty [Bar]	ASA	Size ["]	[R]aised/[F]lat
24.2.1	A	[COL]	Fuel Oil	150	8	R
24.2.2	B	[COL]	Cargo Vapour	150	10	R
24.2.3	C	[COL]	Cargo Liquid	300	14	R
24.2.4	D	[COL]	Cargo Liquid	300	14	R
24.2.5	E	[COL]	Cargo Vapour	150	10	R
24.2.6	F	[COL]	Cargo Vapour	150	10	R
24.2.7	G	[COL]	Cargo Liquid	300	14	R
24.2.8	H	[COL]	Fuel Oil	150	8	R
24.3	Height above uppermost continuous deck	[mm]	2100			
24.4	Distance from ship side	[mm]	4000			
24.5	Height above load waterline	[mm]	11530			
24.6	Height above light waterline	[mm]	18470			

2.25 CARGO REDUCERS

B25	CARGO REDUCERS	CLIPPER SUN
25.0	ANSI 300	ANSI 300 -150
25.1	2 off 16"NB 300# ' 14"NB 300#	2 off 14"NB 300# ' 12"NB 150#
25.2	2 off 14"NB 300# ' 12"NB 300#	2 off 12"NB 300# ' 10"NB 150#
25.3	2 off 14"NB 300# ' 10"NB 300#	2 off 10"NB 300# ' 10"NB 150#
25.4	2 off 14"NB 300# ' 8"NB 300#	2 off 8"NB 300# ' 10"NB 150#
25.5	1 off 14"NB 300# ' 6"NB 300#	2 off 6"NB 300# ' 10"NB 150#
25.6		
25.7		
25.8		
25.9		
25.0	ANSI 150	FUEL
25.1	2 off 12"NB 150# ' 10"NB 150#	1 off 8"NB 150# ' 12"NB 150#
25.2	2 off 10"NB 150# ' 8"NB 150#	1 off 8"NB 150# ' 10"NB 150#
25.3		1 off 8"NB 150# ' 8"NB 150#
25.4		1 off 8"NB 150# ' 6"NB 150#
25.5		
25.6		
25.7		
25.8		
25.9		

2.26 CONNECTION TO SHORE FOR ESD/COM SYSTEMS

B26	CONNECTIONS TO SHORE FOR ESD AND COM. SYSTEMS	UNIT	CLIPPER SUN
26.1	Is ESD connection to Shore available?	[Yes/No]	YES
26.1.1	System	[Text]	Electric
26.1.2	Type of plug	[Text]	6-pin NATO
26.3	Is Hose or cables Available on Board	[Yes/No]	YES
26.3.1	Specify Length	[m]	30
26.3.2	Specify type	[Text]	

2.27 MANIFOLD DERRICK/CRANE

B27	MANIFOLD DERRICK/CRANE	UNIT	CLIPPER SUN
27.1	Is Manifold Derrick Provided?	[Yes/No]	NO
27.2	Is Manifold Crane Provided?	[Yes/No]	YES
27.3	Is Lifting equipment Same P&SB?	[Yes/No]	Central
27.3.1	If NO, give details	[Text]	
27.3.2	Maximum outreach	[m]	6.2
27.3.3	Capacity at max. Outreach	[ton]	10

2.28 STORES HANDLING

B28	STORES HANDLING	UNIT	CLIPPER SUN
28.1	Number of cranes	[Pcs]	2
28.1.1	Location(s)	[Text]	Aft

3. SECTION C – Machinery

3.1 NOX FACTOR TIER II

C1.1	NOx factor	UNIT	CLIPPER SUN
1.1.1.0	Main engine		Tier II
1.1.1.1	Power	[kW]	13560
1.1.1.2	RPM	[RPM]	105
1.1.1.3	NOx limit	[g/kWh]	17
1.1.1.4	NOx factor	[g/kWh]	13.8
1.1.1.5	EIAPP	[Ref]	EIAPP-1495-1-A
1.1.1.6	Issued	[Date]	17.04.2012
1.1.2.0	Auxiliary engine 1		Tier II
1.1.2.1	Power	[kW]	1260
1.1.2.2	RPM	[RPM]	720
1.1.2.3	NOx limit	[g/kWh]	12.1
1.1.2.4	NOx factor	[g/kWh]	10.5
1.1.2.5	EIAPP	[Ref]	EIAPP-144-138-A
1.1.2.6	Issued	[Date]	17.04.2012
1.1.3.0	Auxiliary engine 2		Tier II
1.1.3.1	Power	[kW]	1260
1.1.3.2	RPM	[RPM]	720
1.1.3.3	NOx limit	[g/kWh]	12.1
1.1.3.4	NOx factor	[g/kWh]	10.5
1.1.3.5	EIAPP	[Ref]	EIAPP-144-139-A
1.1.3.6	Issued	[Date]	17.04.2012
1.1.4.0	Auxiliary engine 3		Tier II
1.1.4.1	Power	[kW]	1260
1.1.4.2	RPM	[RPM]	720
1.1.4.3	NOx limit	[g/kWh]	12.1
1.1.4.4	NOx factor	[g/kWh]	10.5
1.1.4.5	EIAPP	[Ref]	EIAPP-144-140-A
1.1.4.6	Issued	[Date]	17.04.2012
1.1.5.0	Auxiliary engine 4		Tier II
1.1.5.1	Power	[kW]	1260
1.1.5.2	RPM	[RPM]	720
1.1.5.3	NOx limit	[g/kWh]	12
1.1.5.4	NOx factor	[g/kWh]	11
1.1.5.5	EIAPP	[Ref]	EIAPP-144-141-A
1.1.5.6	Issued	[Date]	41016

3.2 NOX FACTOR TIER III

C1.2	NOx factor	UNIT	CLIPPER SUN
1.2.1.0	Main engine		Tier III
1.2.1.1	Power	[kW]	0
1.2.1.2	RPM	[RPM]	0
1.2.1.3	NOx limit	[g/kWh]	0
1.2.1.4	NOx factor	[g/kWh]	0
1.2.1.5	EIAPP	[Ref]	0
1.2.1.6	Issued	[Date]	00.01.1900
1.2.2.0	Auxiliary engine 1		Tier III
1.2.2.1	Power	[kW]	0
1.2.2.2	RPM	[RPM]	0
1.2.2.3	NOx limit	[g/kWh]	0
1.2.2.4	NOx factor	[g/kWh]	0
1.2.2.5	EIAPP	[Ref]	0
1.2.2.6	Issued	[Date]	00.01.1900
1.2.3.0	Auxiliary engine 2		Tier III
1.2.3.1	Power	[kW]	0
1.2.3.2	RPM	[RPM]	0
1.2.3.3	NOx limit	[g/kWh]	0
1.2.3.4	NOx factor	[g/kWh]	0
1.2.3.5	EIAPP	[Ref]	0
1.2.3.6	Issued	[Date]	00.01.1900
1.2.4.0	Auxiliary engine 3		Tier III
1.2.4.1	Power	[kW]	0
1.2.4.2	RPM	[RPM]	0
1.2.4.3	NOx limit	[g/kWh]	0
1.2.4.4	NOx factor	[g/kWh]	0
1.2.4.5	EIAPP	[Ref]	0
1.2.4.6	Issued	[Date]	00.01.1900
1.2.5.0	Auxiliary engine 4		Tier III
1.2.5.1	Power	[kW]	1260
1.2.5.2	RPM	[RPM]	720
1.2.5.3	NOx limit	[g/kWh]	12
1.2.5.4	NOx factor	[g/kWh]	11
1.2.5.5	EIAPP	[Ref]	EIAPP-144-141-A
1.2.5.6	Issued	[Date]	41016

3.3 EGCS/SCRUBBER

C2	EGCS/SCRUBBER	UNIT	CLIPPER SUN
2.1.0	Main engine		
2.1.1	Scrubber installed	[Yes/No]	YES
2.1.2	Maker	[Text]	Wärtsila
2.1.3	Type	[Text]	Open-loop
2.1.4	VGP compliant	[Yes/No]	YES
2.2.0	Auxiliary engines		
2.2.1	Scrubber installed	[Yes/No]	YES
2.2.2	Maker	[Text]	Wärtsila
2.2.3	Type	[Text]	Open-loop
2.2.4	VGP compliant	[Yes/No]	YES
2.3.0	Tank capacity closed loop		
2.3.1	NaOH tank	[Days]	0
2.3.2	NaOH tank	[m ³]	0
2.3.3	Sludge tank	[Days]	0
2.3.4	Sludge tank	[m ³]	0
2.3.5	Scrubbing water holding tank	[Days]	0
2.3.6	Scrubbing water holding tank	[m ³]	0

3.4 HEAT RECOVERY

C3	HEAT RECOVERY	UNIT	CLIPPER SUN
3.1.0	Main engine		
3.1.1	Economizer installed	[Yes/No]	YES
3.1.2	Type	[Text]	0
3.1.3	Capacity	[kW]	0
3.1.4	Auxiliary engines		
3.1.5	Economizer installed	[Yes/No]	NO
3.1.6	Type	[Text]	0
3.1.7	Capacity	[kW]	0

3.5 OTHER RELEVANT TECHNICAL INFORMATION


C4	OTHER RELEVANT TECHNICAL INFORMATION	UNIT	CLIPPER SUN
4.0	Rudder type	[Text]	Conventional
4.0.1	Number of rudders	[Pcs]	1
4.1	Type of propeller	[Text]	Fixed propeller
4.1.1	Blades	[Pcs]	4
4.2	Mewis Duct	[Yes/No]	NO
4.3	Ballast Water Treatment System	[Yes/No]	0
4.3.1	Type	[Text]	0
4.4	Oily Water Separator	[Yes/No]	0
4.4.1	Type	[Text]	0
4.4.2	Concentration	[ppm]	0

3.6 ENVIRONMENTAL/PERFORMANCE TECHNOLOGIES INSTALLED


CODE	C5 ENVIRONMENTAL/PERFORMANCE TECHNOLOGIES INSTALLED	UNIT	CLIPPER SUN
5.0	EEDI (Energy Efficiency Design Index)	[-]	6.59
5.1	ESI (Environmental Ship Index)	[-]	17.60
5.2	Electronic Vessel Performance Monitoring	[Yes/No]	0
5.3	Selective Catalytic Reduction	[Yes/No]	0
5.3.1	Urea Storage Tank Capacity	[Days]	0
5.3.2	Urea Storage Tank Capacity	[m ³]	0
5.4	Trim optimization tests	[Yes/No]	0
5.5	Antifouling	[Text]	0

4. APPENDIX/DRAWINGS

4.1 CARGO PUMPS



4.2 BOOSTER PUMPS




4.3 RE-HEATER CAPACITY, AMMONIA




Cargo Heater Capacity for Ammonia

Contract No. : 04014
Client : HHI
Hull No. : Hull No. 1718



4.4 RE-HEATER CAPACITY, PROPANE



4.5 MOORING DIAGRAM

The diagram below illustrates the position of Winch Mounted Wires (W) and Ropes (R) together with Open (O) and Closed (C) Fairleads. Indicate also the position of mooring Bitts (B)

