

GAS FORM-C

CLIPPER MOON



«Industry leading provider of LPG and petrochemical tonnage»

BASED ON:
OCIMF/SIGTTO
Ship Information Questionnaire for Gas Carriers
2nd Edition 1998

CONTENTS

1.	SECTION A – GENERAL INFORMATION	4
1.1	PRINCIPAL SHIP PARTICULARS.....	5
1.2	HULL DIMENSIONS	7
1.3	IMMERSION	7
1.4	LOADED PARTICULARS	7
1.5	PARALLEL MID-BODY DIMENSIONS.....	8
1.6	BUNKER CAPACITIES.....	8
1.7	FUEL CONSUMPTION DETAILS.....	9
1.8	MAIN ENGINE PARTICULARS	9
1.9	AUXILIARY PLANT	9
1.10	POWER/SPEED INFORMATION	10
1.11	THRUSTERS	10
1.12	FRESH WATER.....	10
1.13	BALLAST CAPACITIES AND PUMPS	11
1.14	MOORING	11
1.15	NAVIGATIONAL EQUIPMENT	13
1.16	COMMUNICATIONS EQUIPMENT.....	14
2.	SECTION B – CARGO SYSTEMS.....	15
2.1	GENERAL INFORMATION	16
2.2	CARGO TANKS.....	16
2.3	CARGO TANK CAPACITIES.....	17
2.4	LOADING RATES.....	17
2.5	DISCHARGING – GENERAL	18
2.6	DISCHARGE PRESSURE.....	18
2.7	UNPUMPABLES.....	18
2.8	VAPORISING UNPUMPABLES	18
2.9	RELIQUEFACTION PLANT	19
2.10	COOLING CAPACITY	19
2.11	CARGO TEMP. LOWERING CAPABILITY.....	19
2.12	INERT GAS.....	20
2.13	CARGO TANK INTERTING/DE-INERTING	20
2.14	GAS FREEING TO FRESH AIR	20
2.15	CHANGING CARGO GRADES	20

2.16	DECK TANK CAPACITIES	21
2.17	PRE-LOADING CONDITIONS.....	21
2.18	VAPORISER.....	21
2.19	BLOWER.....	22
2.20	CARGO RE-HEATER	22
2.21	HYDRATE CONTROL	22
2.22	CARGO MEASUREMENT	22
2.23	CARGO SAMPLING	23
2.24	CARGO MANIFOLD	24
2.25	CARGO REDUCERS	25
2.26	CONNECTION TO SHORE FOR ESD/COM SYSTEMS	25
2.27	MANIFOLD DERRICK/CRANE.....	25
2.28	STORES HANDLING	25
3.	APPENDIX/DRAWINGS.....	26
3.1	CARGO PUMPS	27
3.2	BOOSTER PUMPS.....	28
3.3	RE-HEATER CAPACITY, AMMONIA.....	29
3.4	RE-HEATER CAPACITY, PROPANE	30
3.5	MOORING DIAGRAM	31



Solvang ASA dates back to 1936. From very modest beginnings, the shipping company has now developed into one of the world's leading transporters of LPG and petrochemical gases. Solvang ASA has its headquarters in Stavanger, with offices in Oslo and the Philippines.

Solvang has a fleet of modern and efficient vessels - all built in the accordance with the most up to date specifications and fitted with new and efficient technology. Perhaps of greater importance than the modern technology is the way in which the vessels are operated – the people onboard. Good seamanship represents the very core of our business, and we place a firm focus on this area in the form of education, working on attitudes and training.

On every single sailing, we are required to demonstrate the full range of our experience and expertise. Our strength lies in reliable, high-quality deliveries. It is our goal to maintain a steady course towards the future, at the same time as making good use of the experience we have gained.

«Industry leading provider of LPG and petrochemical tonnage»

1. SECTION A – GENERAL INFORMATION

1.1 PRINCIPAL SHIP PARTICULARS

A1	PRINCIPAL SHIP PARTICULARS		CLIPPER MOON
1.0	Date Questionnaire Completed		13.03.2017
1.1	Name of vessel		Clipper Moon
1.2	LR/IMO Number		IMO 9253820
1.3	Last Previous Name		N/A
1.3.1	Date of Name change		N/A
1.4	Second Last Name Change		N/A
1.4.1	Date of Name change		N/A
1.5	Third Last Name Change		N/A
1.5.1	Date of Name change		N/A
1.6	Fourth Last Name Change		N/A
1.6.1	Date of Name change		N/A
1.7	Flag		NIS
1.8	Port Of Registry		Stavanger
1.9	Official Number		
1.10	Call Sign		LAYU5
1.11	VSAT		+ 44 203 145 4161
1.12	Fleet 77		+870 773 233 473
1.13	Fax		+870 763 643 712
1.14	Mini – M		+870 763 643 710
1.15	E-mail		master.clipper.moon@solvangship.no
1.16	GSM Mobile		+47 911 78 571
1.17	SAT C		425892910
1.18	Vessel's MMSI Number		258929000
1.19	Max tank pressure	UNIT	
1.19.1	(1) Pressurized	[bar g]	
1.19.2	(2) Semi- Refrigerated	[bar g]	
1.19.3	(3) Refrigerated	[bar g]	0,275
1.20	Minimum tank temperature	UNIT	
1.20.1	(1) Pressurized	[°C]	
1.20.2	(2) Semi- Refrigerated	[°C]	
1.20.3	(3) Refrigerated	[°C]	-50
A1	OWNERSHIP AND OPERATION		
1.21	REGISTERED OWNER		P/R LGC DA
1.22	Visitor's address		Haakon VII Gate 8
1.22.1	City		N-4005 Stavanger
1.22.2	Country		Norway
1.23	Postal address		P.O. Box 90
1.23.1	City		N-4001 Stavanger
1.23.2	Country		Norway
1.24	Office Telephone Number		+47 51 84 84 00
1.25	Office Fax Number		+47 51 84 84 11
1.26	Office Telex Number		
1.27	Office e-mail Address		solvang-lgc@solvangship.no
1.28	Number of Years Vessel Owned		13,3
1.29	NAME OF TECHNICAL OPERATOR		Solvang ASA
1.30	Visitor's address		Haakon VII Gate 8
1.30.1	City		N-4005 Stavanger
1.30.2	Country		Norway
1.31	Postal address		P.O. Box 90
1.31.1	City		N-4001 Stavanger
1.31.2	Country		Norway
1.32	Office Telephone Number		(+47) 51 84 84 00

1.33	Office Fax Number		(+47) 51 84 84 11
1.34	Office Telex Number		
1.35	Office e-mail Address		solvang-lgc@solvangship.no
1.36	Number of Years as vessel Operator		13,3
1.37	Total number of vessels, Operator		23
1.38	COMMERCIAL OPERATOR		Solvang ASA
1.39	Visitor's address		Haakon VII's gt 6
1.39.1	City		N-0121 Oslo
1.39.2	Country		Norway
1.40	Postal address		P.O.Box 1734 Vika
1.40.1	City		N-0121 Oslo
1.40.2	Country		Norway
1.41	Office Telephone Number		(+47) 22 47 19 50
1.42	Office e-mail Address		chartering@solvangship.no
1.42.1	Office e-mail Address 2		operation@solvangship.no
1.43	Number of Years as vessel Operator		13,3
1.44	Builder		Kawasaki
1.45	Name of Yard Vessel Built At		Sakaide shipyard
1.46	Hull Number		1531
1.47	Date Keel Laid		14.04.2003
1.48	Date Launched		15.05.2003
1.49	Date Delivered		04.12.2003
1.50	Date of Completion of Major Hull Changes (If Any)		N/A
1.51	If Changes were made, specify changes and yard		N/A
A1	CLASSIFICATION	UNIT	CLIPPER MOON
1.52	Classification Society	[Text]	DNV GL
1.53	Class Notation	[Text]	+1A1 TANKER FOR LIQUIFIED GAS
1.53.1	Cont.	[Text]	2G, E0, NALITICUS
1.53.2	Cont.	[Text]	PLUS-1 TMON
1.54	If Class Society Changed, Name of Previous society	[Text]	N/A
1.55	If Class Society Changed, Date of Change	[Date]	N/A
1.56	Built in accordance with Regulations:		Approval recieved
1.56.1	IMO	[Yes/No]	YES
1.56.2	USCG	[Yes/No]	YES
1.56.3	RINA	[Yes/No]	NO
1.56.4	Other	[Yes/No]	NO
1.57	IMO Certification Certificate of Fitness		Approval recieved
1.57.1	IGC	[Yes/No]	YES
1.57.2	A328	[Yes/No]	NO
1.57.3	A329	[Yes/No]	NO
1.57.4	Letter of compliance	[Yes/No]	YES
1.57.5	Issued By	[Text]	DNV GL
1.58	Unattended Machinery Space certificate	[Yes/No]	Yes (24h)
A1	TONNAGES	UNIT	CLIPPER MOON
1.59	Nett Registered Tonnage	[NT]	11053
1.60	Gross Tonnage	[GT]	35012
1.61	Suez Canal Tonnage		
1.61.1	Net Tonnage	[NT]	32205,14
1.61.2	Gross Tonnage	[GT]	36872,31
1.62	Panama Canal Tonnage		
1.62.1	Net Tonnage	[NT]	28998
1.62.2	Gross Tonnage	[GT]	

1.2 HULL DIMENSIONS

A2	HULL DIMENSIONS	UNIT	CLIPPER MOON
2.1	Length Overall	[m]	205,0
2.2	Length Between Perpendiculars	[m]	200,0
2.3	Distance Bow to Bridge	[m]	169,0
2.4	Distance Bridge Front to Mid-Point Manifold	[m]	64,0
2.5	Distance Bow to Mid-Point Manifold	[m]	105,0
2.6	Extreme Breadth	[m]	32,2
2.7	Extreme Depth	[m]	20,2
2.8	Summer Draught	[m]	12,0
2.9	Corresponding Deadweight	[ton]	44822,0
2.10	Light Displacement/weight	[ton]	15859,0
2.11	Loaded Displacement (Summer)	[ton]	60681,0
2.12	Cargo Tank Cubic Capacity (100% full)	[m3]	58197,0
2.13	Distance from Keel to Highest Point (With mast down)	[m]	47,7
2.14	Air Draught normal ballast (With mast down)	[m]	40,7


1.3 IMMERSION

A3	IMMERSION	UNIT	CLIPPER MOON
3.1	Normal Ballast Draught	[TPC]	52,30
3.1.1	Draught	[m]	7
3.2	Loaded Draught	[TPC]	56,5
3.2.1	Draught	[m]	12

1.4 LOADED PARTICULARS

A4	LOADED PARTICULARS	UNIT	CLIPPER MOON		
4.1	Cargo:		Propane	VCM	Ammonia
4.2	Density:	[ton/m3]	0,58		0,6815
4.3	Cargo	[ton]	33700,00		39500
4.4	Bunkers	[ton]	3518,45		3518,44565
4.5	DO	[ton]			
4.6	Fresh Water	[ton]	260,00		260
4.7	Stores/Spares	[ton]	150		150
4.8	Lube Oil	[ton]	70		80
4.9	Ballast	[ton]	1035		700
4.10	Deadweight Const.	[ton]	38615		44100,00
4.11	Draught – Forward	[m]	10,4		11,7
4.11.1	Aft	[m]	11,3		12,1
4.11.2	Equiv.	[m]	10,9		11,9

1.5 PARALLEL MID-BODY DIMENSIONS



A5	PARALLEL MID-BODY DIMENSIONS	UNIT	CLIPPER MOON
5.1	A Manifold to FWD	[m]	105,00
5.2	B Manifold to AFT	[m]	100
5.3	Loaded draft equiv-		
5.3.1	C Manifold to FWD side tangent line	[m]	36,4
5.3.2	D Manifold to AFT side tangent line	[m]	57,7
5.4	Ballast draft equiv.		
5.4.1	E Manifold to FWD	[m]	36,2
5.4.2	F Manifold to AFT	[m]	49,8

1.6 BUNKER CAPACITIES

A6	BUNKER CAPACITIES	UNIT	CLIPPER MOON
6.1	HFO	[Grade]	IFO 380 (Standard)
6.1.1	Capacity @ 100 %	[m3]	2522,1
6.2	LSHFO	[Grade]	N/A
6.2.1	Capacity @ 100 %	[m3]	N/A
6.3	Diesel Oil	[Grade]	D0
6.3.1	Capacity @ 100 %	[m3]	1135,6

1.7 FUEL CONSUMPTION DETAILS

Average speed and consumption, based on max force 4 Beaufort and 15% Sea Margin.

Vessel use mainly HFO for all consumers. DO/GO for INCN and when Rules & Regulations demands it for other consumers

A7	FUEL CONSUMPTION DETAILS	UNIT	CLIPPER MOON
7.1	LOADED CONDITION		*About
7.2	Average speed over 12 months	[kn]	16,00
7.3	Average consumption, Main engine	[ton/day]	43
7.4	Consumption, AUX		
7.4.1	Butane	[ton/day]	4,5
7.4.2	Ammonia	[ton/day]	4-9
7.5	Average consumption, AUX		
7.5.1	Ammonia	[ton/day]	4,5
7.5.2		[ton/day]	6
7.6	BALLAST CONDITION		
7.7	Average speed over 12 months	[kn]	16
7.8	Average consumption, Main engine	[ton/day]	41
7.9	Average consumption, AUX	[ton/day]	4
7.10	PORT/IDLE		
7.11	Average consumption, AUX, Loading	[ton/day]	8,5
7.12	Average consumption, AUX, Discharging	[ton/day]	6
7.13	Average consumption, AUX, Idle	[ton/day]	3,5
7.14	Average consumption, Boiler (depending on weather)	[ton/day]	2,0-3,0
7.15	OTHER		
7.16	INCN (When operating) - MDO/MGO	[ton/day]	0,2
7.17	IGG-plant (When operating)	[ton/day]	0,2
7.18	ME CONSUMPTION GRAPH/KNOTS		LOADED BALLAST
7.18.1	16.2	[ton/day]	47,0 45,0
7.18.2	16	[ton/day]	43,0 41,0
7.18.3	15	[ton/day]	34,0 32,0
7.18.4	14	[ton/day]	25,0 23,0
7.18.5	12	[ton/day]	18,0 17,0

1.8 MAIN ENGINE PARTICULARS

A8	MAIN ENGINE PARTICULARS	UNIT	CLIPPER MOON
8.1	Main Engine Make and Type	[Text]	KAWASAKI-MAN B&W 5S60MC-C
8.2	No of Units	Pcs	1
8.3	Maximum Continuous Rating (MCR)	[kW]	11275
8.3.1	RPM	[RPM]	105
8.4	Total Available Power	kW	11 275
8.5	Normal service Power	kW	10 147

1.9 AUXILIARY PLANT

A9	AUXILIARY PLANT	UNIT	CLIPPER MOON
9.1	Make and Type of Auxiliary Generators	[Text]	MAN B&W Holeby 8L23/30h
9.2	Main Generators	[Pcs]	
9.2.1	No of Units	[Pcs]	2
9.2.2	Maximum Generator Output per Unit	[kW]	1 470
9.3	Generators, other	[Yes/No]	MAN B&W Holeby 5L23/30

9.3.1	No of Units	[Pcs]	1
9.3.2	Maximum Generator Output per Unit	[kW]	1 050
9.4	Shaft Generator	[kW]	N/A
9.5	Total Available Power	[kW]	3990
9.6	Emergency Generator	[kW]	200
9.7	Emergency Fire Pump	[Text]	
9.7.1	Type	[Text]	Vertical Centrifugal
9.7.2	Delivery Pressure	[Bar]	10
9.7.3	Motive Power	[Text]	Electric
9.7.4	If Electrical, Indicate Power Required in kW	[kW]	45
9.8	Steering Gear Type		Cylinder
9.8.1	kW to Steer the Vessel with One Pump Unit	[kW]	15

1.10 POWER/SPEED INFORMATION

A10	POWER/SPEED INFORMATION	UNIT	CLIPPER MOON
10.1	Trial Data		
10.1.1	NCR	[kW]	10 200
10.1.2	MCR	[kW]	11 150
10.1.3	Speed	[kn]	17,55
10.1.4	Draught	[m]	6,04
10.2	Normal Service Speed		
10.2.1	NCR	[kW]	10150
10.2.2	MCR	[kW]	11275
10.2.3	Speed	[kn]	16,5
10.2.4	Draught	[m]	7

1.11 THRUSTERS

A11	THRUSTERS	UNIT	CLIPPER MOON
11.1	Make and Type	[Text]	Kawasaki KT-157B3
11.2	No. Installed	[Pcs]	1,00
11.3	Location and Rated Bollard Pull or kW output	[kW]	1200

1.12 FRESH WATER

A12	FRESH WATER	UNIT	CLIPPER MOON
12.1	Capacity of Distilled Tanks	[ton]	N/A
12.2	Capacity of F/D.W. Ts	[ton]	262,00
12.3	Daily Consumption	[ton/day]	10,00
12.4	Daily Evaporator Output	[ton/day]	25,00

1.13 BALLAST CAPACITIES AND PUMPS

A13	BALLAST CAPACITIES AND PUMPS	UNIT	CLIPPER MOON	
13.1	Tank Capacities		Capacity [m3]	Tanks [Pcs]
13.1.1	Forepeak	[Col]	693,30	1
13.1.2	Wing or Side tanks	[Col]	14218	8
13.1.3	Aft Peak	[Col]	602,3	1
13.1.4	Other	[Col]		
13.1.5	Other	[Col]		
13.1.6	Total	[Col]	15 513,60	10
13.2	Ballast Pumps			
13.2.1	Capacity per pump	[m3/h]	800	
13.2.2	Model	[Text]	SVA300MU	
13.2.3	Type	[Text]	Electric	
13.2.4	Setting	[Text]	Vertical Centrifugal	
13.3	No of Pumps	[Pcs]	2	
13.4	Total Capacity	[m3/h]	1600	
13.5	Location	[Text]	Engine Room	
13.6	Control Location	[Text]	CCR, Engine Room, Bridge	

1.14 MOORING

A14	MOORING EQUIPMENT	UNIT	CLIPPER MOON			
14.1	Mooring wires (On drums)		FWD	FWD DECK	AFT DECK	POOP
14.1.1	Number	[Pcs]				
14.1.2	Diameter	[mm]				
14.1.3	Length	[m]				
14.1.4	Maximum Breaking Load	[ton]				
14.2	Mooring wire tails		FWD	FWD DECK	AFT DECK	POOP
14.2.1	Number	[Pcs]				
14.2.2	Type	[Text]				
14.2.3	Diameter	[mm]				
14.2.4	Length	[m]				
14.2.5	Maximum Breaking Load	[ton]				
14.3	Mooring ropes (On drums)		FWD	FWD DECK	AFT DECK	POOP
14.3.1	Number	[Pcs]	6	2	2	6
14.3.2	Type	[Text]	MAXI-CARAT	MAXI-CARAT	MAXI-CARAT	MAXI-CARAT
14.3.3	Diameter	[mm]	68	64	64	64
14.3.4	Length	[m]	220	220	220	220
14.3.5	Maximum Breaking Load	[ton]	88	88	88	88
14.4	Mooring winches		FWD	FWD DECK	AFT DECK	POOP
14.4.1	Number	[Pcs]	3	1	1	3
14.4.2	[S]ingle/[D]ouble drums	[S/D]	Double	Double	Double	Double
14.4.3	Split drums	[Yes/No]	YES	YES	YES	YES
14.4.4	Motive power	[Text]	Hydraulic	Hydraulic	Hydraulic	Hydraulic
14.4.5	Heaving power	[ton]	20	20	15	20
14.4.6	Brake capacity	[ton]	50	50	50	50
14.4.7	Hauling speed	[m/s]	0,25	0,25	0,25	0,25
14.5	Wires/ropes not on drums		WIRES	ROPES	EM'GENCY	
14.5.1	Number	[Pcs]		2/2		
14.5.2	Type	[Text]		MAXI-CARAT		
14.5.3	Diameter	[mm]		68		
14.5.4	Length	[m]		220		

14.5.5	Maximum Breaking Load	[ton]	88
--------	-----------------------	-------	----

A14	ANCHORS AND WINDLASSES	UNIT	CLIPPER MOON
14.5.1	Windlass Motive Power (e.g. Steam, Hydraulic)	[Text]	Hydraulic
14.5.2	Hauling Power	[ton]	20
14.5.3	Brake Holding Power	[ton]	67
14.5.4	Anchor Type	[Text]	HHP Stockless OAC-14 type
14.5.5	Weight	[kg]	7 585
14.5.6	Is Spare Carried	[Yes/No]	YES
14.5.7	Cable Diameter	[mm]	78
14.5.8	No of Shackles Port	[Pcs]	12
14.5.9	No of Shackles Starboard	[Pcs]	12
14.6	TOWING EQUIPMENT		
14.6.1	Is Ship fitted with a Towing Bracket AFT(drum)	[Yes/No]	YES
14.6.2	If Yes, state SWL	[ton]	100
14.6.3	Is Towing Chain provided	[Yes/No]	YES
14.6.4	Dimensions of Towing Wire - Diameter	[mm]	57
14.6.5	Length	[m]	80
14.7	Windage on Ballast Draught		
14.7.1	End-on	[m2]	489
14.7.2	Lateral	[m2]	3110

Mooring diagram is provided in the appendix.

1.15 NAVIGATIONAL EQUIPMENT

A15	NAVIGATIONAL EQUIPMENT	UNIT	CLIPPER MOON
15.1	Magnetic Compass	[Yes/No]	YES
15.2	Off Course Alarm – Magnetic	[Yes/No]	YES
15.3	Gyro Compass	[Yes/No]	YES
15.3.1	Specify number	[Pcs]	2
15.4	Off Course Alarm – Gyro	[Yes/No]	YES
15.5	Bridge Repeaters	[Yes/No]	YES
15.5.1	Specify Number	[Pcs]	3
15.6	Radar 3 GHz	[Yes/No]	YES
15.7	Radar 9 GHz	[Yes/No]	YES
15.8	Are Radars Gyro Stabilized	[Yes/No]	YES
15.9	Radar Plotting Equipment	[Yes/No]	YES
15.10	ARPA	[Yes/No]	YES
15.11	ECDIS (Electric Display and Information System)	[Yes/No]	YES
15.11.1	Make/Type	[Text]	Transas
15.12	Depth Echo Sounder with Recorder	[Yes/No]	YES
15.13	Depth Echo Sounder without Recorder	[Yes/No]	NO
15.14	Speed/Distance Indicator	[Yes/No]	YES
15.15	Doppler Log	[Yes/No]	YES
15.16	Speed of Approach Doppler	[Yes/No]	YES
15.17	Rudder Angle Indicator	[Yes/No]	YES
15.18	Rudder Angle Indicator on Each Bridge Wing	[Yes/No]	YES
15.19	R.P.M Indicator	[Yes/No]	YES
15.20	R.P.M Indicator on Each Bridge Wing	[Yes/No]	YES
15.21	Controllable Propeller Pitch Indicator	[Yes/No]	NO
15.22	Thruster (s) indicator	[Yes/No]	YES
15.23	Rate of turn Indicator	[Yes/No]	YES
15.24	Radio Direction Finder	[Yes/No]	NO
15.25	NAVTEX Receiver	[Yes/No]	YES
15.26	GPS	[Yes/No]	YES
15.27	Transit SATNAV	[Yes/No]	NO
15.28	DECCA navigator	[Yes/No]	NO
15.29	Omega	[Yes/No]	NO
15.30	Loran C	[Yes/No]	NO
15.31	Weather Route System	[Yes/No]	YES
15.32	Sextant(s)	[Yes/No]	YES
15.33	Signal Lamp ALDIS	[Yes/No]	YES
15.34	Anemometer	[Yes/No]	YES
15.35	Engine Order Recorder	[Yes/No]	YES
15.36	Course Recorder	[Yes/No]	YES
15.37	Steering motor controls controls fitted on bridge wings	[Yes/No]	YES
15.38	Is bridge Equipped with a “Dead Man” Alarm Equipment	[Yes/No]	YES
15.39	What chart outfit coverage is provided	[Yes/No]	
15.39.1	Worldwide	[Yes/No]	YES
15.39.2	Limited	[Yes/No]	NO
15.39.3	If Limited Please Indicate	[Text]	
15.40	Formal Chart Correction System in use	[Yes/No]	
15.41	Electronic Chart System in use	[Yes/No]	YES

1.16 COMMUNICATIONS EQUIPMENT

A16	COMMUNICATIONS EQUIPMENT	UNIT	CLIPPER MOON
16.1	Main Transmitted Including Radio Telephone Distress Frequency	[Yes/No]	YES
16.2	Main Receiver Including Radio Telephone Distress Frequency	[Yes/No]	YES
16.3	Radio Telephone Distress Frequency Watch Receiver	[Yes/No]	YES
16.4	Main Radio Antenna	[Yes/No]	YES
16.5	Reserve Radio Antenna	[Yes/No]	NO
16.6	Main and Reserve Installations Electrically Separate and Independent	[Yes/No]	YES
16.7	2182 kHz Bridge auto Alarm	[Yes/No]	YES
16.8	Alarm Signal Generating Device	[Yes/No]	YES
16.9	VHF Radio (s)	[Yes/No]	YES
16.9.1	Specify Number	[Pcs]	3
16.10	Portable VHF/UHF Radios	[Yes/No]	YES
16.10.1	Specify Type and Number	[Pcs]	
16.11	Are Sets Intrinsically Safe	[Yes/No]	YES
16.12	Inmarsat Satellite System	[Yes/No]	YES
16.13	Specify System Type A, B, C, F or VSAT	[Text]	C
16.14	Is the ship equipped as per GMDSS Requirements	[Yes/No]	YES
16.15	If Yes, which area of operation is vessel certified to operate in	[Text]	
16.15.1	EPIRB	[Yes/No]	YES
16.15.2	SARTS	[Yes/No]	YES
16.16	Emergency Lifeboat Transceiver	[Yes/No]	YES
16.17	At least Three Survival craft Two-way Radio Telephone Apparatus	[Yes/No]	YES
16.18	Full Set of Publications	[Yes/No]	YES

2. SECTION B – CARGO SYSTEMS

2.1 GENERAL INFORMATION

B1	CARGO - GENERAL INFORMATION		CLIPPER MOON	
1.1	List Products Which the Ship is Certified to Carry			
1.1.1	1.	Ammonia		
1.1.2	2.	Butane		
1.1.3	3.	Butane/propane		
1.1.4	4.	Butadiene		
1.1.5	5.	Butylene		
1.1.6	6.	Propane		
1.1.7	7.	Propylene		
1.1.8	8.			
1.1.9	9.			
1.1.10	10.			
1.1.11	11.			
1.1.12	12.			
1.1.13	13.			
1.1.14	14.			
1.1.15	15.			
1.1.16	16.			
1.1.17	17.			
1.1.18	18.			
1.1.19	19.			
1.1.20	20.			
1.1.21	21.			
1.1.22	22.			
1.1.23	23.			
1.1.24	24.			
1.2	Transport and Carriage Condition		UNIT	
1.3	Minimum Allowable Tank Temperature		[Celsius]	-50
1.3.1	Maximum Allowable Tank Pressure (Seagoing setting)		[bar g]	0,275
1.3.2	Maximum Allowable Tank Pressure (Harbour setting)		[bar g]	0,4
1.4	Grades which can be Loaded or Discharged Simultaneously		[Pcs]	2
1.5	Grades which can be Transported Simultaneously		[Pcs]	2
1.6	Number of Products Re-liquefied Simultaneously		[Pcs]	2
1.7	State Natural Tank Segregations (Possible combinations)		UNIT	
1.7.1	1.		[Tank]	2 & 1+3+4
1.7.2	2.		[Tank]	1+3 & 2+4
1.7.3	3.		[Tank]	1+2+3+4

2.2 CARGO TANKS

B2	CARGO TANKS	UNIT	CLIPPER MOON
2.1	Cargo Tanks		
2.1.1	Type	[Text]	Type A
2.1.2	Material	[Text]	Carbon Manganese LT
2.2	Maximum Allowable Relief Valve setting	[bar g]	0,4
2.3	Safety Valve Set Pressure – If Variable Give Range of Pilot Valves		
2.3.1	Seagoing setting	[bar g]	0,275
2.3.2	Harbour setting	[bar g]	0,4
2.4	Maximum Vacuum	[bar g]	0,25
2.5	Maximum Cargo Density (98% full)	[kg/m3]	685
2.6	Maximum Rate of Cool-Down	[C/h]	10

2.7	State any Limitations regarding Partially Filled Tanks	[Text]	NO
2.7.1	Cont.	[Text]	
2.8	State Allowable Combinations of Filled and Empty Tanks	[Text]	NO
2.8.1	Cont.	[Text]	

2.3 CARGO TANK CAPACITIES

B3	CARGO TANK CAPACITIES	UNIT	CLIPPER MOON				
3.1	Capacity	Tank	1	2	3	4	Total
3.1.1	100 %	[m3]	14444	14862	14848	15231	59385
3.1.2	98 %	[m3]	14155	14565	14551	14926	58197
3.2	Cargo						
3.2.1	iso-butane	[ton]	8408	8651	8643	8866	34569
3.2.2	Propane	[ton]	8210	8448	8440	8657	33754
3.2.3	Butadiene	[ton]	9215	9482	9473	9717	37886
3.2.4	Propylene	[ton]	8635	8885	8876	9105	35500
3.2.5	Ammonia	[ton]	9625	9904	9895	10150	39574
3.2.6	Butylene/Butenes	[ton]	8408	8651	8643	8866	34569
3.2.7	n-butane	[ton]	8507	8753	8745	8971	34977
3.2.8	Ethylene	[ton]					

- Cargoes may not be applicable for this vessel. Check which cargoes the vessel is certified to carry.

2.4 LOADING RATES

VR = Vapour Return, W/O VPR = Without Vapour Return

B4	LOADING RATES	UNIT	CLIPPER MOON			
			REFRIGERATED		PRESSURE	
4.1	Cargo	[m3/h]	VR	W/O VR	VR	W/O VR
4.1.1	1 Butane	[m3/h]	2300	2000		
4.1.2	2 Propane	[m3/h]	2300	1600		
4.1.3	3 Ammonia	[m3/h]	2300	1600		
4.1.4	4 Butane (0-30°C)	[m3/h]			1000	1000
4.1.5	5 Propane (0°C)	[m3/h]			200	200
4.1.6	6 Propane (10°C)	[m3/h]			100	100
4.1.7	7 Propane (20°C)	[m3/h]			80	50
4.1.8	8 Propane (30°C)	[m3/h]				
4.1.9	9	[m3/h]				
4.1.10	10	[m3/h]				
4.1.11	11	[m3/h]				
4.1.12	12	[m3/h]				
4.1.13	13	[m3/h]				
4.1.14	14	[m3/h]				
4.1.15	15	[m3/h]				
4.1.16	16	[m3/h]				
4.1.17	17	[m3/h]				
4.1.18	18	[m3/h]				
4.1.19	19	[m3/h]				
4.1.20	20	[m3/h]				

2.5 DISCHARGING – GENERAL

Pumping curves for cargo main pumps and booster pumps are given in the appendix.

B5	DISCHARGING – GENERAL	UNIT	CLIPPER MOON
5.1	Cargo Pumps	[Text]	Deepwell
5.1.1	Type of Pumps	[Text]	Centrifugal
5.1.2	Number per Tank	[Pcs]	2
5.1.3	Rate (per pump)	[m3/h]	500
5.1.4	Delivery Head	[mlc]	130
5.1.5	Maximum Density	[kg/m3]	685
5.2	Booster Pumps		
5.2.1	Type of Pumps	[Text]	Centrifugal
5.2.2	Number	[Pcs]	2
5.2.3	Rate (per pump)	[m3/h]	500
5.2.4	Delivery Head	[mlc]	130
5.2.5	Maximum Density	[kg/m3]	685

2.6 DISCHARGE PRESSURE

B6	DISCHARGE PERFORMANCE	UNIT	CLIPPER MOON	
6.1	Fully Refrigerated, Full Cargo Discharge Times (all pumps):		VR	W/O VR
6.1.1	Manifold Back Pressure (1 kg/cm2) x	[h]	24	24
6.1.2	Manifold Back Pressure (5 kg/cm2) x	[h]	30	30
6.1.3	Manifold Back Pressure (10 kg/cm2) ^	[h]	50	50
6.2	Pressurized, Full Cargo Discharge Times (all pumps):		VR	W/O VR
6.2.1	Manifold Back Pressure (1 kg/cm2) ^	[h]		
6.2.2	Manifold Back Pressure (5 kg/cm2) ^	[h]		
6.2.3	Manifold Back Pressure (10 kg/cm2) ^	[h]		

x = Based on largest single tank volume

^ = Based on discharging tanks one at a time

2.7 UNPUMPABLES

B7	UNPUMPABLES	UNIT	CLIPPER MOON
7.1	Unpumpables, liquid		
7.1.1	Tank 1	[m3]	8
7.1.2	Tank 2	[m3]	8
7.1.3	Tank 3	[m3]	8
7.1.4	Tank 4	[m3]	8
7.1.5	Total	[m3]	32

2.8 VAPORISING UNPUMPABLES

B8	VAPORISING UNPUMPABLES	UNIT	CLIPPER MOON
8.1	Process Used	[Text]	Hot Gas / Puddle heating
8.2	Time to Vaporize Liquid Unpumpables After Discharge:		
8.2.1	Propane	[h]	8
8.2.2	Butane	[h]	10
8.2.3	Ammonia	[h]	12
8.2.4		[h]	
8.2.5		[h]	

2.9 RELIQUEFACTION PLANT

B9	RELIQUEFACTION PLANT	UNIT	CLIPPER MOON
9.1	Plant Design Conditions		
9.1.1	Air Temperature	[°C]	45
9.1.2	Sea Temperature	[°C]	32
9.2	Plant Type		
9.2.1	Single Stage/Direct	[Yes/No]	NO
9.2.2	Two Stage / Direct	[Yes/No]	YES
9.2.3	Three Stage / Direct	[Yes/No]	YES
9.2.4	Coolant Type	[Text]	Seawater
9.3	Compressors		
9.3.1	Type	[Text]	Sulzer + Burckhardt
9.3.2	Model	[Text]	3K140-3A
9.3.3	Number	[Psc]	4
9.3.4	Capacity (per unit)	[m3/h]	Varies
9.3.5	Are they oil free?	[Yes/No]	YES

2.10 COOLING CAPACITY

B10	COOLING CAPACITY	UNIT	CLIPPER MOON	
10.1	State Cooling Capacity (per compressor, 2-stage @ - 0.4 bar g)		SW 32 [°C]	SW 15 [°C]
10.1.1	1 Propane @ -42 [°C]	[kcal/h]	480000	
10.1.2	2 Propane @ -20 [°C]	[kcal/h]	1049011	
10.1.3	3 Propane @ -5 [°C]	[kcal/h]	1100602	
10.1.4	4 Butane @ -42 [°C]	[kcal/h]		
10.1.5	5 Butane @ -20 [°C]	[kcal/h]		
10.1.6	6 Butane @ -5 [°C]	[kcal/h]	480000	
10.1.7	7	[kcal/h]		

2.11 CARGO TEMP. LOWERING CAPABILITY

B11	CARGO TEMPERATURE LOWERING CAPABILITY	UNIT	CLIPPER MOON
11.0	Time taken to lower the temp of:		
11.1	Propane from ...0 [°C] to -42 [°C]	[h]	
11.2	-5 [°C] to -42 [°C]	[h]	
11.3	-38 [°C] to -42 [°C]	[h]	48
11.4	+20 [°C] to -0.5 [°C]	[h]	
11.5	+10 [°C] to -0.5 [°C]	[h]	
11.6	Butane from +20 [°C] to -0.5 [°C]	[h]	48
11.7	+10 [°C] to -0.5 [°C]	[h]	30
11.8	+10 [°C] to -5 [°C]	[h]	40
11.9	Butadiene from +20 [°C] to -5 [°C]	[h]	
11.10	Propylene from -20 [°C] to -47 [°C]	[h]	
11.11	Ammonia from -15 [°C] to -33 [°C]	[h]	

2.12 INERT GAS

B12	INERT GAS	UNIT	CLIPPER MOON
12.1	Main IG Plant		
12.1.1	Type of System	[Text]	Gas Oil Burning
12.1.2	Capacity	[m3/h]	5500
12.1.3	Type of Fuel Used	[Text]	MDO/MGO
12.1.4	Composition of I.G.		
12.1.5	Max O2	[%]	0,5
12.1.6	Max CO2	[%]	15
12.1.7	Max Nox	[%]	Traces
12.1.8	Max N2	[%]	Balance
12.2	Lowest Dewpoint Achievable	[°C]	-40
12.3	Used for	[Text]	
12.4	Auxiliary IG or Nitrogen Plant		
12.4.1	Type of System	[Text]	Buffer tank
12.4.2	Capacity	[m3/h]	20
12.5	Lowest Dewpoint Achievable	[°C]	-25
12.6	Used for	[Text]	Void Space padding
12.7	Nitrogen generator installed?	[Yes/No]	NO
12.7.1	Liquid storage Capacity	[m3]	N/A
12.7.2	Daily Boil-Off Loss	[m3]	N/A
12.7.3	Maximum Supply Pressure	[Bar]	N/A
12.7.4	Supply Capacity	[m3/h]	N/A
12.7.5	Used For	[Text]	N/A
12.7.6	HP Nitrogen	[Nm3]	N/A

2.13 CARGO TANK INTERTING/DE-INERTING

B13	CARGO TANK INTERTING/DE-INERTING	UNIT	CLIPPER MOON
13.1	Time Taken From Fresh Air to Under 5% O2 at -25oC Dewpoint	[h]	24
13.2	Time taken from cargo Vapor to Fully Inert at - 25oC Dewpoint when:		
13.2.1	IG density less than product	[h]	36
13.2.2	IG density greater than product	[h]	48

2.14 GAS FREEING TO FRESH AIR

B14	GAS FREEING TO FRESH AIR	UNIT	CLIPPER MOON
14.1	Plant Used	[Text]	Blowers
14.1.1	Number of fans	[Pcs]	2
14.1.2	Total capacity	[m3/h]	20000
14.2	Time taken from Fully Inert Condition to Fully Breathable Air	[h]	24

2.15 CHANGING CARGO GRADES

The table below show the number of hours needed to change grades from the removal of unpumpables to tanks fit to load. The quantity of inert gas consumed during the operation is also indicated.

B15	CHANGING CARGO GRADES	UNIT	CLIPPER MOON	
15.1	From propane to:		[h]	[m3]
15.1.1	Iso-butane	[COL]	36	88500
15.1.2	Ammonia	[COL]	130	88500
15.2	From Iso-butane to:		[h]	[m3]
15.2.1	Propane	[COL]	36	88500
15.2.2	Ammonia	[COL]	130	88500
15.3	From ammonia to:		[h]	[m3]
15.3.1	Propane	[COL]	140	88500
15.3.2	Iso-butane	[COL]	120	88500

2.16 DECK TANK CAPACITIES

B16	DECK TANK CAPACITIES	UNIT	CLIPPER MOON
16.1	Deck tank	[Yes/No]	NO
16.2	Deck tank capacities		N/A
16.2.1	1 Propane	[ton]	N/A
16.2.2	2 Ammonia	[ton]	N/A
16.2.3	3 Ethylene	[ton]	N/A
16.3	Maximum Allowable Relief Valve Setting	[bar g]	N/A
16.4	Lowest Permissible Temperature	[°C]	N/A
16.5	Materials	[Text]	N/A

2.17 PRE-LOADING CONDITIONS

The table below indicates time and quantity of coolant required to cool down cargo tanks from ambient temperature and fully gassed up state sufficient to allow loading to commence.

B17	PRE-LOADING CONDITIONS	UNIT	CLIPPER MOON		
17.1	Product		Quantity [ton]	VPR [h]	W/O VPR [h]
17.1.1	Propane	[COL]	400	24	48
17.1.2	Butane	[COL]	400	24	24
17.1.3	Butadiene	[COL]	420	24	36
17.1.4	Propylene	[COL]	400	36	48
17.1.5	Ammonia	[COL]	450	24	48
17.1.6	VCM	[COL]			

2.18 VAPORISER

B18	VAPORISER	UNIT	CLIPPER MOON
18.1	Type of Vaporizer	[Text]	Shell and tube
18.2	Number Fitted	[Pcs]	1
18.3	Capacity (per unit) – Propane	[Nm3/h]	4000
18.3.1	Liquid Supply rate	[m3/h]	10
18.3.2	Delivery temperature	[°C]	-10
18.4	Capacity (per unit) – Ammonia	[Nm3/h]	3600
18.4.1	Liquid Supply rate	[m3/h]	10
18.4.2	Delivery temperature	[°C]	
18.5		[Nm3/h]	
18.5.1		[m3/h]	
18.5.2		[°C]	

2.19 BLOWER

B19	BLOWER	UNIT	CLIPPER MOON
19.1	Type of Blower	[Text]	Electrical
19.2	Number fitted	[Pcs]	2
19.3	Rated Capacity (per unit)	[Nm ³ /h]	20000
19.4	Delivery Pressure	[Bar]	1

2.20 CARGO RE-HEATER

Cargo re-heater capacities are given in the appendix.

B20	CARGO RE-HEATER	UNIT	CLIPPER MOON
20.1	Type of re-heater	[Text]	Shell/tube
20.2	Number Fitted	[Pcs]	1
20.3	Heating Medium	[Medium]	Seawater
20.4	Discharge rates, SW = 15[°C], to raise product temperature:		
20.4.1	Propane from -42[°C] to 0[°C]	[ton/h]	500
20.4.2	Ammonia from -33[°C] to 0[°C]	[ton/h]	335
20.5	Cargo Heater Curve:	[Yes/No]	YES

2.21 HYDRATE CONTROL

B21	HYDRATE CONTROL	UNIT	CLIPPER MOON
21.1	Type of Depressant	[Medium]	Other
21.2	Depressant Freezing Point Temperature	[°C]	-70
21.3	Max capacity of depressant	[Liter]	5000
21.4	Means of Injection	[Text]	Hand pump
21.5	Any other system used	[Text]	

2.22 CARGO MEASUREMENT


B22	CARGO MEASUREMENT	UNIT	CLIPPER MOON
22.1	Level Gauges		
22.1.1	Are level gauges Local or Remote	[Text]	Remote Electronic Radar
22.1.2	Manufacturer	[Text]	Radar GL-100 KMSS-AS
22.1.3	Type	[Text]	Radar
22.1.4	Rated Accuracy	[-]	± 5 mm
22.1.5	Certifying Authority	[Text]	DNV
22.2	Temperature Transmitter		
22.2.1	Manufacturer	[Text]	KMSS AS
22.2.2	Type	[Text]	PT100 (AL-100A/18 ex)
22.2.3	Rated Accuracy	[-]	0.15+0.002
22.2.4	Certifying Authority	[Text]	DNV
22.3	Pressure Transmitter		
22.3.1	Manufacturer	[Text]	KMSS AS
22.3.2	Type	[Text]	GT300 to GT304
22.3.3	Rated Accuracy	[-]	
22.3.4	Certifying Authority	[Text]	DNV
22.4	Oxygen Analyzer		

22.4.1	Manufacturer	[Text]	Servomex
22.4.2	Type	[Text]	XENDOS 1800
22.4.3	Lowest Level Measurable		0.01% O2
22.5	Fixed Gas Analyzer		
22.5.1	Manufacturer	[Text]	Bravida
22.5.2	Type	[Text]	Catalytic/LFG 7-19-870 IGP
22.6	Cargo Tank Calibration Tables		
22.6.1	Are Cargo Tank Calibration tables available	[Yes/No]	YES
22.6.2	Measuring Company	[Text]	NKKK
22.6.3	Certifying Authority	[Text]	DNV
22.6.4	Calibration calculated tocm ½ cm.....	[Yes/No]	YES
22.6.5	Tables established tocmcm.....mm	[Yes/No]	CM
22.6.6	Trim and List corrections Available	[YES/NO]	YES
22.6.7	Temperature Corrections available	[YES/NO]	YES
22.6.8	Float Gauge Tape Corrections Available	[YES/NO]	YES

2.23 CARGO SAMPLING

B23	CARGO SAMPLING	UNIT	CLIPPER MOON			
23.1	Cargo tank sample level	[Tank]	1	2	3	4
23.1.1	Top	[Yes/No]	Yes	Yes	Yes	Yes
23.1.2	Middle	[Yes/No]	Yes	Yes	Yes	Yes
23.1.3	Bottom	[Yes/No]	Yes	Yes	Yes	Yes
23.2	Can sample be drawn from?					
23.2.1	Tank Vapor Outlet	[Yes/No]	YES			
23.2.2	Manifold Liquid Line	[Yes/No]	YES			
23.2.3	Manifold Vapor Line	[Yes/No]	YES			
23.2.4	Pump Discharge Line	[Yes/No]	YES			
23.3	State connection					
23.3.1	Type	[Text]	Male screw type			
23.3.2	Size	[Inch]	0,5			

2.24 CARGO MANIFOLD



B24	CARGO MANIFOLD	UNIT	CLIPPER MOON			
24.1	Distance from center of manifold to:					
24.1.1	Stern	[m]	101,68			
24.1.2	Bow	[m]	103,28			
24.1.3	A	[mm]	9250			
24.1.4	B	[mm]	8250			
24.1.5	C	[mm]	3750			
24.1.6	D	[mm]	1250			
24.1.7	E	[mm]	1250			
24.1.8	F	[mm]	3750			
24.1.9	G	[mm]	5000			
24.1.10	H	[mm]	5750			
24.2	Flange		Duty [Bar]	ASA	Size ["]	[R]aised/[F]lat
24.2.1	A	[COL]	Fuel Oil	100	8	F
24.2.2	B	[COL]	Fuel Oil	100	6	F
24.2.3	C	[COL]	Cargo Liquid	250	14	R
24.2.4	D	[COL]	Cargo Vapour	100	10	R
24.2.5	E	[COL]	Cargo Vapour	100	10	R
24.2.6	F	[COL]	Cargo Liquid	250	14	R
24.2.7	G	[COL]	Other	100	13	F
24.2.8	H	[COL]	Fuel Oil	100	8	F
24.3	Height above uppermost continuous deck	[mm]	1250			
24.4	Distance from ship side	[mm]	3500			
24.5	Height above load waterline	[mm]	10000			
24.6	Height above light waterline	[mm]	14100			

2.25 CARGO REDUCERS

B25	CARGO REDUCERS	CLIPPER MOON
25.0	ANSI 300	ANSI 300 -150
25.1	2 off 14"NB 300# ' 12"NB 300#	2 off 14"NB 300# ' 16"NB 150#
25.2	2 off 14"NB 300# ' 10"NB 300#	2 off 14"NB 300# ' 14"NB 150#
25.3	2 off 14"NB 300# ' 8"NB 300#	2 off 14"NB 300# ' 12"NB 150#
25.4	1 off 14"NB 300# ' 6"NB 300#	2 off 14"NB 300# ' 10"NB 150#
25.5		2 off 14"NB 300# ' 8"NB 150#
25.6		
25.7		
25.8		
25.9		
25.0	ANSI 150	FUEL
25.1	2 off 10"NB 150# ' 12"NB 150#	
25.2	2 off 10"NB 150# ' 8"NB 150#	
25.3	2 off 10"NB 150# ' 6"NB 150#	
25.4		
25.5		
25.6		
25.7		
25.8		
25.9		

2.26 CONNECTION TO SHORE FOR ESD/COM SYSTEMS

B26	CONNECTIONS TO SHORE FOR ESD AND COM. SYSTEMS	UNIT	CLIPPER MOON
26.1	Is ESD connection to Shore available?	[Yes/No]	YES
26.1.1	System	[Text]	MTL 901
26.1.2	Type of plug	[Text]	SPDT 6 Pin Plug
26.3	Is Hose or cables Available on Board	[Yes/No]	YES
26.3.1	Specify Length	[m]	30
26.3.2	Specify type	[Text]	electric

2.27 MANIFOLD DERRICK/CRANE

B27	MANIFOLD DERRICK/CRANE	UNIT	CLIPPER MOON
27.1	Is Manifold Derrick Provided?	[Yes/No]	NO
27.2	Is Manifold Crane Provided?	[Yes/No]	YES
27.3	Is Lifting equipment Same P&SB?	[Yes/No]	NO
27.3.1	If NO, give details	[Text]	Center
27.3.2	Maximum outreach	[m]	22,5
27.3.3	Capacity at max. Outreach	[ton]	7,5

2.28 STORES HANDLING

B28	STORES HANDLING	UNIT	CLIPPER MOON
28.1	Number of cranes	[Pcs]	2
28.1.1	Location(s)	[Text]	Aft

3. APPENDIX/DRAWINGS

3.1 CARGO PUMPS

Fig. 10.1 Performance curve - Deepwell pumps





Fig. 10.1

3.2 BOOSTER PUMPS

Fig. 10.2 Performance curve - Booster pumps



3.3 RE-HEATER CAPACITY, AMMONIA

AMMO...A

HEATING CAPACITY
FLOW RATE


Inlet temperature -33 °C
Outlet temperature 0 °C

Cargo Heater


HamworthyKSE type 210/274/128.3/2U TI
Tube bundle in Titanium, U type

Example:

Sea water consumption = 800 m³/h
Sea water temperature = 15 °C
The cargo to be heated from -33 °C to 0 °C at discharging.
Found capacity = 335 m³/h (Sea water at 15 °C)




Note:
Sea water discharge temperature should not be less than 5.5 °C



Date	Sign.	Scale	Capacity Diagram
Draw. 10.08.01	JDM		Cargo Heater
Design 10.08.01	JDM		210/274/128.3/2U TI
Check 10.08.01	TK		
HamworthyKSE Norway			Index 00
			Date 10.08.01
			TU 17812-758
			Page: 1 of 1

3.4 RE-HEATER CAPACITY, PROPANE



3.5 MOORING DIAGRAM

